Poliflex tools

PUR bond





Poliflex blocks PUR

The rhomboidal shape even enables work to be effortlessly performed on hard-to-reach places such as corners

With a diamond cut-off wheel, the blocks can be minimized and adapted to the respective application as required.

Matching tool drives:

manual application

Ordering notes:

■ Please complete the description with the desired grit size.

L	В	Н	Grit size			\Longrightarrow	Description
[mm]	[mm]	[mm]	60 120 240				
				EAN 4007220			
115	60	30	298671	298688	298695	5	PFB 1156030 CU PUR



Poliflex block set PSO PUR

Set of different Poliflex blocks PUR.

Contents:

9 units in total, 3 Poliflex blocks from each category

- Grit 60 (coarse)
- Grit 120 (medium)
- Grit 240 (fine)


Α	dν	′ar	١ta	ıa	es	

Promotional display box.

Matching tool drives:

manual application

L x B x H [mm]	EAN 4007220		Description
285 x 150 x 60	298886	1	PSO 11560



Poliflex marbling tool holders PFZY PUR

Tools with female thread M8 for marbling surfaces.

Recommendations for use:

For face-down grinding, use at 1,000–4,000 RPM.

Matching tool drives:

flexible shaft drive, straight grinder

Ordering notes:

- Please order the matching arbor separately.
- Please complete the description with the desired grit size.

D	D T Thread		Grit size		Opt.	Max.	Suitable	\Longrightarrow	Description
[mm]	[mm]		30	80	RPM	RPM	arbors		
			EAN 4007220						
50	40	M8	146194	146200	1,000–4,000	5,700	BO 6/8	5	PF ZY 5040 M8 CN PUR



Arbors BO

Matching arbor for Poliflex marbling tool holders PFZY.

Advantages:

■ High economic efficiency as the tool can be changed quickly.

S [mm]	L [mm]	Thread	EAN 4007220		Description
6	40	M8	062104	1	BO 6/8