






Specifications

Connector Shell Material	Nickel-plated brass
Connector Insert Material	Nylon
Contact Type	Machined brass with gold over nickel plating
Wire Insulation	Oil resistant PVC, 22 AWG stranded copper, 300V
Operating Temperature [C (F)]	-20...+105° (-4...+221°)

Features

- Male bulkhead receptacles
- 4-, 5- or 8-pin DC micro configuration
- M16, M20 or 1/2 inch-14 NPT mounting threads

Product Selection

Face View of Male	Wire Color	Wire Rating	Length [m (ft)]	Panel Mount Thread Size	Drawing	Cat. No.
	1 Brown 2 White 3 Blue 4 Black	22 AWG 300V 3 A	0.1 (0.3)	M16 x 1	A	888D-M4AC9-4N
				M20 x 1.5	B	888D-M4AC8-4N
	1 Brown 2 White 3 Blue 4 Black 5 Grey		0.3 (1)	1/2 inch-14 NPT	C	888D-M4AC1-0M3
			0.1 (0.3)	M16 x 1	A	888D-M5AC9-4N
				M20 x 1.5	B	888D-M5AC8-4N
	1 Red/White Tr 2 Red 3 Green 4 Red/Yellow Tr 5 Red/Black Tr 6 Red/Blue Tr	22 AWG 300V 3 A	0.1 (0.3)	M16 x 1	A	888R-M6AC9-4N
				M20 x 1.5	B	888R-M6AC8-4N
			0.3 (1)	1/2 inch-14 NPT	C	888R-M6AC1-0M3
					1 White 2 Brown 3 Green 4 Yellow 5 Grey 6 Pink 7 Blue 8 Red	24 AWG 36V DC/30V AC 1.5 A
M20 x 1.5	B	888D-M8AC8-4N				

Approximate Dimensions

Dimensions are shown in mm (in.). Dimensions are not intended to be used for installation purposes.

