


# Quick coupling plug KS4-N-6

Part number: 2152

FESTO



 General operating condition

## Data sheet

| Feature                                              | Value                                     |
|------------------------------------------------------|-------------------------------------------|
| Nominal size                                         | 4.5 mm                                    |
| Operating pressure complete temperature range        | -0.095 MPa ... 1.2 MPa                    |
| Operating pressure complete temperature range        | -0.95 bar ... 12 bar                      |
| Operating pressure complete temperature range        | -13.775 psi ... 174 psi                   |
| Standard nominal flow rate                           | 441 l/min ... 495 l/min                   |
| Nominal flow rate standardised according to ISO 8778 | 478 l/min ... 536.6 l/min                 |
| Operating medium                                     | Compressed air to ISO 8573-1:2010 [7:-:-] |
| Note on operating and pilot medium                   | Lubricated operation possible             |
| Corrosion resistance class CRC                       | 1 - Low corrosion stress                  |
| LABS (PWIS) conformity                               | VDMA24364-B1/B2-L                         |
| Ambient temperature                                  | -10 °C ... 60 °C                          |
| Product weight                                       | 15 g                                      |
| Pneumatic connection, port 1                         | Barbed hose fitting 6 mm                  |
| Note on materials                                    | RoHS-compliant                            |
| Information on materials                             | Brass, nickel plated                      |