

Type : 3EL112M2C-PD-B0-C34

RE: 891432

Date : 03.01.2022

Power [kW]	: 4.00	Efficiency Class	: IE3
Input Voltage [V]	: 400	Duty Cycle	: S1
Connection Type [Δ / Y]	: Δ	Service Factor	: 1.20
Frequency [Hz]	: 50	Frame Size	: 112M
Pole Number	: 2	Weight [kg]	: 29.1
Nominal Speed [rpm]	: 2915	Insulation Class	: F [155°C]
Nominal Current [A]	: 7.28	Temperature Rise	: B [80°K]
Nominal Moment [Nm]	: 13.1	Protection Class	: IP55
Nominal Efficiency [η]	: 88.1	Vibration Severity Grade	: A
Power Factor [$\cos\phi$]	: 0.90	Method of Cooling	: IC411
Locked Rotor Current [I_a/I_n]	: 7.5	Direction of Rotation	: Bidirectional
Locked Rotor Torque [Ma/Mn]	: 2.6	Balance	: Half Key
Breakdown Torque [Mk/Mn]	: 3.9	Motor Protection	: --
Motor Color	: RAL 7031	Altitude Above Sea Level	: 1000m
Ambient Temperature	: -15°C / +40°C	Sound Pressure Level [dBA]	: 65

ELECTRICAL DATA

Δ / Y	U [V]	f [Hz]	P [kW]	n [rpm]	I [A]	η [%]	$\cos\phi$
Δ	400	50	4.00	2915	7.28	88.1	0.90
Y	690	50	4.00	2915	4.20	88.1	0.90
Δ	460	60	4.64	3500	7.07	89.5	0.92


MECHANICAL DATA

Moment of Inertia [kgm ²]	: 0.00618
Bearing DS / NS	: 6206ZZ / 6206ZZ
Frame Material	: Aluminum
Flange Type / Material	: B3 / Aluminum
Cooling Fan Material	: Plastic
End Shield Material	: Aluminum

TERMINAL BOX

Terminal Box Material	: Aluminum
Terminal Box Position	: Top
Terminal Box Cable Entry	: M25x1.5
Terminal Box Blind Cap	: M25x1.5
Contact Screw Thread	: M5

MECHANICAL DIMENSIONS



FLANGE TYPE	D	E	L	AC	H	HE	HD	F	GA	DB	C	ØK	B	BB	HA	AA	A	AB
B3	28	60	390	215	112	161	273	8	31	M10	70	12	140	177	4	36	190	217

Manufactured and tested in accordance with IEC 60034

*Technical data are subject to change! There may be discrepancies between calculated and rating plate values.

*MECALINE has right to change all the data without prior notice.

FR.AG.010 REV. NO: 03 REV TARİHİ : 01.01.2021

Europe

Rubix Engineering
61 Avenue Tony Garnier
69007, Lyon
France

UK

Dakota House, Concord Business Park
Manchester M22 0RR
UK