

## Product Information

# 14 26 160

## Diagonal Insulation Stripper

- With long cutter
- High cutting capacity due to high transmission ratio
- Precision stripping holes for single conductors of 1.5 and 2.5 mm<sup>2</sup>
- Convenient cutting of NYM cables up to 5 x 2.5 mm<sup>2</sup>
- Long tips for ultra fine cutting work also in confined areas
- Induction-hardened precision blades, cutting edge hardness approx. 60 HRC



⚡ 1000V

| General                                        |                                                  |
|------------------------------------------------|--------------------------------------------------|
| Article No.                                    | 14 26 160                                        |
| EAN                                            | 4003773040279                                    |
| pliers                                         | chrome-plated                                    |
| head                                           | chrome-plated                                    |
| handles                                        | insulated with multi-component grips, VDE-tested |
| Weight                                         | 238 g                                            |
| Dimensions                                     | 160 x 60 x 30 mm                                 |
| Standard                                       | DIN EN 60900 IEC 60900                           |
| REACH compliant                                | does not contain SVHC                            |
| RoHS compliant                                 | not applicable                                   |
| Technical details                              |                                                  |
| Cutting capacities soft wire (diameter)        | Ø 2.5 mm                                         |
| Cutting capacities medium hard wire (diameter) | Ø 1.5 mm                                         |
| Stripping capacities in square millimetres     | 1.5 / 2.5 mm <sup>2</sup>                        |
| AWG                                            | 16 / 14                                          |
| VDE tested                                     | yes                                              |

Technical changes and errors excepted

