

# Push-in fitting NPQH-D-M5-S4-P10

Part number: 578358

FESTO



 [General operating condition](#)

## Data sheet

| Feature                                       | Value                                                                                    |
|-----------------------------------------------|------------------------------------------------------------------------------------------|
| Size                                          | Standard                                                                                 |
| Nominal size                                  | 2.5 mm                                                                                   |
| Type of seal on screwed plug                  | Sealing ring                                                                             |
| Mounting position                             | optional                                                                                 |
| Design                                        | Straight design                                                                          |
| Size of pack                                  | 10                                                                                       |
| Design                                        | Push-pull principle                                                                      |
| Symbol                                        | 00997424                                                                                 |
| Operating pressure complete temperature range | -0.095 MPa ... 2 MPa                                                                     |
| Operating pressure complete temperature range | -0.95 bar ... 20 bar                                                                     |
| Operating pressure complete temperature range | -13.775 psi ... 290 psi                                                                  |
| Note on operating pressure                    | Water: max. 0.6 MPa at 0 - 50 °C                                                         |
| Certificate issuing authority                 | NSF C0523185                                                                             |
| Operating medium                              | Compressed air to ISO 8573-1:2010 [7:-:-]<br>Water (liquid, ice-free)                    |
| Note on operating and pilot medium            | Lubricated operation possible                                                            |
| Corrosion resistance class CRC                | 3 - high corrosion stress                                                                |
| LABS (PWIS) conformity                        | VDMA24364-B1/B2-L                                                                        |
| Cleanroom class                               | Element installed statically, no meaningful evaluation possible according to ISO 14644-1 |
| Suitable for use with food                    | See declaration of conformity<br>NSF/ANSI 169                                            |
| Ambient temperature                           | 0 °C ... 150 °C                                                                          |
| Nominal torque                                | 1 Nm                                                                                     |
| Tolerance for nominal tightening torque       | ± 20%                                                                                    |
| Product weight                                | 3.3 g                                                                                    |
| Type of mounting                              | External hexagon, A/F 9 mm                                                               |
| Pneumatic connection, port 1                  | Male thread M5                                                                           |
| Pneumatic connection, port 2                  | Push-in sleeve Ø 4 mm                                                                    |
| Note on materials                             | RoHS-compliant                                                                           |
| Material housing                              | Brass, chemically nickel-plated                                                          |
| Material thread seal                          | FPM                                                                                      |