


# End plate VMPAL-EPL-FL40-IP40

Part number: 560942

FESTO



 General operating condition

## Data sheet

| Feature                                              | Value                               |
|------------------------------------------------------|-------------------------------------|
| Width                                                | 43 mm                               |
| Length                                               | 107.3 mm                            |
| Max. number of valve positions                       | 32                                  |
| Valve terminal structure                             | Valve sizes can be mixed            |
| Max. number of valve coils                           | 32                                  |
| Operating pressure                                   | -0.09 MPa ... 1 MPa                 |
| Operating pressure                                   | -0.9 bar ... 10 bar                 |
| Pilot pressure                                       | 0.3 MPa ... 0.8 MPa                 |
| Pilot pressure                                       | 3 bar ... 8 bar                     |
| Nominal operating voltage DC                         | 24 V                                |
| Corrosion resistance class CRC                       | 3 - high corrosion stress           |
| LABS (PWIS) conformity                               | VDMA24364-B1/B2-L                   |
| Degree of protection                                 | IP40                                |
| Note on degree of protection                         | In assembled state                  |
| Ambient temperature                                  | -5 °C ... 50 °C                     |
| Product weight                                       | 190 g                               |
| Electrical connection 1, function                    | Multi-pin plug                      |
| Electrical connection 1, connection type             | Plugs                               |
| Electrical connection 1, connector system            | Connection pattern FC               |
| Electrical connection 1, number of connections/cores | 40                                  |
| Note on materials                                    | RoHS-compliant                      |
| Material end plate                                   | Die-cast aluminium<br>PA-reinforced |