



## Scotch-Brite™ Precision Radial Bristle Brush

<b>Product Description</b>	<p>Scotch-Brite Bristle segments are stacked to assemble the brush to a desired width. These polymeric bushes have the abrasive mineral distributed throughout the resin for a 3-dimensional product. This means that as the brush wears, fresh minerals are always exposed.</p> <p>They are used on parts with complex geometries for:          Deburring – Removing small burrs in difficult to reach areas          Blending – Refining or generating a grain pattern on a part          Cleaning – Removing surface contaminants, rust, adhesive, weld burn          Coating Removal – Removing paint, primer, and other coatings.</p>																																									
<b>Mineral</b>	<p>3M Precision-Shaped Grain (PSG) or PSG / Alumina Zirconia blend.</p>																																									
<b>Bristle Design</b>	<p>TS Straight, rigid and aggressive. Can be run in either direction.</p> <p>TA Angled, rigid and aggressive bristle design. Like type S, but for smaller diameters</p> <p>TC Curved, the softest and most flexible bristle design.</p> <p>TA and TC must be run in the direction of the Bristle angle.</p>																																									
<b>Dimensions/ Grades</b>	<table border="1" data-bbox="337 1146 1300 1472"> <thead> <tr> <th colspan="2">Outside Diameter</th> <th>Grade</th> <th>Color</th> <th>Bristle Type</th> </tr> </thead> <tbody> <tr> <td colspan="2" rowspan="3">3" (76 mm)</td> <td>50+</td> <td>Neon Green</td> <td>TA</td> </tr> <tr> <td>80+</td> <td>Orange</td> <td>TA / TC</td> </tr> <tr> <td>120+</td> <td>Gray</td> <td>TA / TC</td> </tr> <tr> <td colspan="2" rowspan="3">6" (152 mm)</td> <td>50+</td> <td>Neon Green</td> <td>TA</td> </tr> <tr> <td>80+</td> <td>Orange</td> <td>TA / TC</td> </tr> <tr> <td>120+</td> <td>Gray</td> <td>TA / TC</td> </tr> <tr> <td rowspan="3">TC: 7-5/8" (194 mm)</td> <td rowspan="3">TS: 8" (203 mm)</td> <td>50+</td> <td>Neon Green</td> <td>TS</td> </tr> <tr> <td>80+</td> <td>Orange</td> <td>TS / TC</td> </tr> <tr> <td>120+</td> <td>Gray</td> <td>TS / TC</td> </tr> </tbody> </table>				Outside Diameter		Grade	Color	Bristle Type	3" (76 mm)		50+	Neon Green	TA	80+	Orange	TA / TC	120+	Gray	TA / TC	6" (152 mm)		50+	Neon Green	TA	80+	Orange	TA / TC	120+	Gray	TA / TC	TC: 7-5/8" (194 mm)	TS: 8" (203 mm)	50+	Neon Green	TS	80+	Orange	TS / TC	120+	Gray	TS / TC
Outside Diameter		Grade	Color	Bristle Type																																						
3" (76 mm)		50+	Neon Green	TA																																						
		80+	Orange	TA / TC																																						
		120+	Gray	TA / TC																																						
6" (152 mm)		50+	Neon Green	TA																																						
		80+	Orange	TA / TC																																						
		120+	Gray	TA / TC																																						
TC: 7-5/8" (194 mm)	TS: 8" (203 mm)	50+	Neon Green	TS																																						
		80+	Orange	TS / TC																																						
		120+	Gray	TS / TC																																						
<b>Safety</b>	<p>Always use appropriate PPE and follow safety precautions as instructed in the associated Product Safety Insert. Product Safety Inserts are included with shipped products and are also available on-line through 3M.com.</p>																																									

**IMPORTANT NOTICE TO PURCHASER:**

**Technical Information:** The technical information, guidance, and other statements contained in this document or otherwise provided by 3M are based upon records, tests, or experience that 3M believes to be reliable, but the accuracy, completeness, and representative nature of such information is not guaranteed. Such information is intended for people with knowledge and technical skills sufficient to assess and apply their own informed judgment to the information. No license under any 3M or third party intellectual property rights is granted or implied with this information.

**Product Selection and Use:** Many factors beyond 3M's control and uniquely within user's knowledge and control can affect the use and performance of a 3M product in a particular application. As a result, customer is solely responsible for evaluating the product and determining whether it is appropriate and suitable for customer's application, including conducting a workplace hazard assessment and reviewing all applicable regulations and standards (e.g., OSHA, ANSI, etc.). Failure to properly evaluate, select, and use a 3M product and appropriate safety products, or to meet all applicable safety regulations, may result in injury, sickness, death, and/or harm to property.

**Warranty, Limited Remedy, and Disclaimer:** Unless a different warranty is specifically stated on the applicable 3M product packaging or product literature (in which case such warranty governs), 3M warrants that each 3M product meets the applicable 3M product specification at the time 3M ships the product. 3M MAKES NO OTHER WARRANTIES OR CONDITIONS, EXPRESS OR IMPLIED, INCLUDING, BUT NOT LIMITED TO, ANY IMPLIED WARRANTY OR CONDITION OF MERCHANTABILITY, FITNESS FOR A PARTICULAR PURPOSE, OR ARISING OUT OF A COURSE OF DEALING, CUSTOM, OR USAGE OF TRADE. If a 3M product does not conform to this warranty, then the sole and exclusive remedy is, at 3M's option, replacement of the 3M product or refund of the purchase price.

**Limitation of Liability:** Except for the limited remedy stated above, and except to the extent prohibited by law, 3M will not be liable for any loss or damage arising from or related to the 3M product, whether direct, indirect, special, incidental, or consequential (including, but not limited to, lost profits or business opportunity), regardless of the legal or equitable theory asserted, including, but not limited to, warranty, contract, negligence, or strict liability.



Abrasive Systems Division  
3M Center Building 240-1-01  
Saint Paul, MN 55144

1-866-279-1235  
[www.3M.com/abrasives](http://www.3M.com/abrasives)

3M is a trademark of 3M.  
Please recycle. © 3M 2024. All rights reserved.