

DESCRIPTION

Johnstone's Trade Acrylic Durable Eggshell is a premium quality, low VOC, mid sheen coating that provides an extremely tough, stain resistant finish, ideal for all high traffic areas. Tested to meet Class 1 ISO 11998 for scrub resistance, it provides a low odour, quick drying finish that is resistant to condensation and regular cleaning, making it ideal for kitchens, bathrooms, schools, hospitals, food production areas, and public buildings.

RECOMMENDED USES



Suitable for interior use.

TYPE OF SUBSTRATE

Wood, metal and plaster. Also suitable for use on wallboards, concrete, cement rendering, brickwork and blockwork in internal situations.

COLOUR RANGE

Over 16,000 colours are available via the Johnstone's Tinting System.

FINISH

Mid sheen.

VOLUME SOLID

36%

COVERAGE



Up to 16 square metres per litre depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1-2 hours.
Recoat after 3-4 hours.

TRANSPORTATION & STORAGE

Avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU Limit Value for this product (Cat A/a): 30g/l (2010).
This product contains max 10g/l VOC.

FILM THICKNESS

Wet: 83µm, dry: 30µm.

KEY PROPERTIES

- Mould resistant formulation*
- Extremely tough and stain resistant
- Class 1 scrub resistance to ISO 11998
- Ideal for use in kitchens and bathrooms
- Mid Sheen finish & non yellowing

* Johnstone's Trade Acrylic Durable Eggshell contains a biocide to protect paint surface from mould degradation.

PREPARATION

Apply all products in accordance with BS 6150: Code of practice for painting of buildings. All surfaces to be painted should be clean, dry and free from loose and flaking material. Prime certain bare surfaces with the appropriate Johnstone's Trade Primer. Rub down previously gloss painted surfaces with fine waterproof abrasive paper and rinse thoroughly before applying a pre-coat of Johnstone's Trade Joncryl Water Based Primer Undercoat. Avoid the inhalation of dust. Wear a suitable face mask if dry sanding. Special precautions should be taken during surface preparation of pre-1960's paint surfaces over wood and metal as they may contain harmful lead. For more information and free Johnstones Trade datasheets call 01924 354945 or visit www.johnstonestrade.com.

APPLICATION



Stir well. Easy to apply by brush or roller. Seal absorbent surfaces with a coat of Acrylic Eggshell thinned up to 10% with clean water. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains reaction mass of: 5-chloro-2-methyl-4-isothiazolin-3-one (EC no.247-500-7) and 2-methyl-2H-isothiazol-3-one (EC no.220-239-6) (3:1), octhlinone (ISO) and 1,2-benzisothiazol-3(2H)-one.
- May produce an allergic reaction.
- Keep out of reach of children.
- If medical advice is needed, have product container or label at hand.
- Do not get in eyes, on skin, or on clothing.
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.
- Dispose of contents and container in accordance with all local, regional, national and international regulations.
- Safety data sheet available on request.
- Contains Biocidal Product: Mixture of CMIT/MIT (3:1) Contains PT7 Film Preservative: OIT

SIZES

2.5 Litre, 5 Litre.