active in all fields of industry.

Filters

into any type of vessel for SMC filters. suited to the application in the vessel.



Elements					
Element	Series	Material	Nominal filtration accuracy (µm)	Main applications	Page
Sintered metal	ЕВ	Bronze	1, 2, 5, 10 20, 40, 70 100, 120	All types of gases/liquids,	
	ES	Stainless steel 316	1, 2, 5, 10 20, 40, 70 100, 120	General solvents, High-temperature fluids	P.41
○ Fiber (Honeycomb)	ЕН	Cotton	0.5, 1, 5, 10 20, 50, 75, 100	General solvents, General neutral fluids	
	ЕНМ	Polypropylene	0.5, 1, 5, 10 20, 50, 75, 100	Plating fluids, General acids, Alkali fluids, Industrial water, Cooling water	P.41
	ЕНК	Glass fiber	1, 5, 10, 20	General acids, High-temperature fluids	
Paper	EP	Cotton, Phenol impregnated, (Epoxy adhesion)	5, 10, 20	Hydraulic oil, Lubricating oil, Fuel oil	P.42
Micromesh	EM100	Stainless steel 304 (Epoxy adhesion)	5, 10, 20, 40 74, 105	All types of gases/liquids,	P.42
	EM500	Stainless steel 316	5, 10, 20, 40 74, 105	High-temperature fluids	1 .42

SMC

21

FGE FGG

FGD

FGA FGC

FGF FGH

FQ1

FN EB□ ES□

Standard Elements Paper / Micromesh

Paper Elements

 Cartridges are pleated for a large filtration area, and elements are economical due to their long service life.

Main applications


Ideal for filtration of hydraulic oil, lubricating oil, fuel oil, oils for the liquid gas industry, dry inert gases, and dry air.



Specifications

Material	Filter paper (Cotton, Phenol resin impregnated paper)
Operating temperature (C°)	0 to 80
Nominal filtration accuracy (μm)	5, 10, 20
Max. differential pressure resistance	0.6 MPa
Jointing material	Epoxy resin
Element replacement differential pressure	0.1 MPa
Element category of How to Order	Р

How to Order Elements



Paper element

Element size

Symbol	Element size	
100	ø65 x L250	
200	ø65 x L500	
300	ø65 x L750	
400	ø65 x L1000	

Seal material Symbol Seal material

N	NBH
V	FKM

Nominal filtration accuracy (µm) Symbol Nominal filtration accuracy (µm)

	Symbol	Nominal filtration accuracy (µm)
	005	5
	010	10
	020	20

Micromesh Elements

- Stainless steel metal mesh has high filtration accuracy.
- Outstanding heat and chemical resistance. Applicable to a wide range of applications.
- Pleated type has 3 times the filtration area of a cylinder.
- Filters are economical because they can be cleaned and repeatedly used.

Main applications

Please use 40 microns or less as a highprecision filter, and 74 microns or higher as a high-grade strainer. All types of gases and fluids, high-temperature fluids.



Specifications

opecinications -				
Model		EM100	EM500	
Materials		Stainless steel 304	Stainless steel 316	
Jointing material		Epoxy resin	_	
Operating temperature (C°) Note 2)		0 to 100	0 to 150	
Nominal filtration accuracy (μm)		5, 10, 20, 40, 74, 105		
Max. differential pressure resistance		0.7 MPa		
Element replacement differential pressure		0.1 MPa		
Chemical resistance	Acid	Cannot be used.	Can be used. Note 1)	
	Alkali	Can be used.	Can be used.	
Element category of How to Order		М	L	

Note 1) Cannot be used with hydrochloric acid, hydrofluoric acid or phosphoric acid. Note 2) Varies depending on the seal material used.

How to Order Elements

EM 500 - 074 A

Micromesh element symbol

Group symbol

Symbol Group symbol
100 Stainless steel 304
500 Stainless steel 316

Nominal filtration accuracy (um)

Nonlina intration accuracy (μπ)				
	Symbol	Nominal filtration accuracy (µm)		
	005	5		
	010	10		
	020	20		
	040	40		
	074	74		
	105	105		

(Size ø65 x L250)



Seal material/Operating temperaturerange

,	Seai materiai	Operating temperature range (°C)
A Note)		0 to 150
T Note)	Fluororesin	0 to 120
N	NBR	0 to 80
٧	FKM	0 to 120

Note) Not possible with EM100 (Stainless steel 304)