

DESCRIPTION

Johnstone's Stormshield Textured Masonry is a premium quality, acrylic resin based paint formulated for exterior use on cement rendering, rough cast, brick and concrete. It provides a fine sand textured finish that bridges hair-line cracks and helps to disguise uneven surfaces.

RECOMMENDED USES



Suitable for exterior use.

TYPE OF SUBSTRATE

Concrete, cement rendering, brick, stone, blockwork and pebble dash.

COLOUR RANGE

Tintable to a range of colours available in the Johnstone's Trade Colour Card.

FINISH

Textured.

VOLUME SOLID

40%

COVERAGE



Approximately 6–8 square metres per litre, depending on the nature and porosity of the surface.

DRYING TIME



Touch dry in 1–2 hours.
Recoat after 4–6 hours.

TRANSPORTATION & STORAGE

To avoid the risk of spillage, always store and transport in a secure upright position. Protect from frost.

THINNER

Clean water.

VOC CONTENT

Low VOC content 0.3-7.99%
VOC's (Volatile Organic Compounds) contribute to atmospheric pollution.

EU limit value for this product (Cat A/c): 40g/l (2010).
This product contains max 30g/l VOC.

FILM THICKNESS

Wet: 143µm, dry: 57µm.

KEY PROPERTIES

- Expected life in excess of 10 years.
- A high quality water-borne acrylic resin based textured finish.
- Masks surface imperfections on exterior surfaces.
- Excellent colour retention.

PREPARATION

All surfaces to be painted should be clean, dry and free from loose and flaking material. Repair cracks and defective areas and treat fungal or algal growth with Johnstone's Sterilisation Wash as directed. Stabilise surfaces of a highly porous or friable nature with Johnstone's Stormshield Stabilising Solution or Johnstone's Quick Dry Stabilising Solution as directed. Wear a suitable face mask when creating dust. For further advice contact Technical Advisory, on 01924 354354.

APPLICATION



Stir well. Easy to apply by brush or roller.
Also suitable for application by adapted conventional spray. If more than one can of a colour is to be used in the same area, intermix before use. Do not apply in temperatures below 10°C or when rain is imminent.

CLEANING



Remove as much product as possible from application equipment before cleaning. Replace lid firmly. Clean equipment immediately after use with warm soapy water and rinse thoroughly. Some local authorities have special facilities for the disposal of waste coatings. Do not empty product into drains or watercourses.

PRECAUTIONS

- Contains 1,2-benzisothiazol-3(2H)-one. May produce an allergic reaction.
- Safety data sheet available on request.
- If medical advice is needed, have product container or label at hand.
- Keep out of reach of children.
- Dispose of contents/container to a waste disposal site in accordance with local/national regulations.
- Ensure good ventilation during application and drying.
- Do not breathe spray. Wear respiratory protection.
- Do not get in eyes, on skin, or on clothing
- IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.
- IF ON SKIN: Wash with plenty of water. Do not use solvent thinners or White Spirit.
- IF SWALLOWED: Call a POISON CENTRE or doctor if you feel unwell.

SIZES

5 Litre.



The British Board of Agrément is designated by Government to issue European Technical Approvals based on the assessment of products for construction. Johnstone's products carrying this logo have undergone rigorous independent testing and received approval from the BBA.