

## Interlocking Floor Tiles

**IDEAL FOR FLOOR  
REFURBISHMENT**

### Tough-Lock

#### A smart solution for floor refurbishment

Interlocking tile manufactured from resilient PVC. - Available in two finishes – Studded and Textured. - Effective for refurbishing floors, such as covering damaged surfaces. - Suitable for heavy and light industrial use, as well as commercial locations. - Can withstand the weight of most forklift trucks. - Tile system simply interlocks for easy installation. - Available in Anti-Static and ESD versions on request. - Bevelled edging available. - Product Height: 5mm or 7mm



Studded Tile	Black	Grey	Blue	Red	Green	Yellow
0.5m x 0.5m x 7mm	TLS010002H	TLS060002H	TLS020002H	TLS030002H	TLS040002H	TLS070002H



Textured Tile	Black	Grey	Blue	Red	Green	Yellow
0.5m x 0.5m x 5mm	TLT010003H	TLT060003H	TLT030003H	TLT040003H	TLT070003H	TLT070003H
Textured Tile	Black	Grey	Blue	Red	Green	Yellow
0.5m x 0.5m x 7mm	TLT010002H	TLT060002H	TLT020002H	TLT030002H	TLT060002H	TLT070002H



### Tough-Lock Eco

#### 100% Recycled economical floor covering

Smart interlocking tile manufactured from 100% recycled PVC. - Studded surface design. - Effective for refurbishing floors, such as covering damaged surfaces. - Suitable for heavy and light industrial use, as well as commercial locations. - Can withstand the weight of most forklift trucks. - Tile system simply interlocks for easy installation. - Bevelled edging available. - Product Height: 5mm

Tile Size (pack of 4)	Black
500mm x 500mm	TLS010001E
Edging (pack of 4)	Black
Bevelled Edge 515mm x 80mm x 5mm	TLE010001E
Bevelled Corner Edge 515mm x 80mm x 5mm	TLC010001E

### Studded Tile

#### Classic floor tile design

Hardwearing natural/synthetic rubber floor tile with studded design. - Popular for many commercial environments. - Raised studs provide some slip-resistance underfoot. - Free from PVC, Plasticizers and Formaldehyde. - Applied by adhesion to the floor. - Product Height: 2.5mm +/- 0.2mm



Tile Size	Black	Light Grey	Dark Grey	Blue	Oyster White
485mm x 485mm (+/- 1mm)	SRTA104	SRTA105	SRTA106	SRTA116	SRTA117