

Catalogue No: 440P-CRPS11B

LMT SW SAFETY 22mm PL ROLLER PLUNGER 1NC 1NO M20

Field Switching and Sensing > Limit Switches > Limit Switches > Allen-Bradley Limit Switches > Bulletin 440P IEC-Style Safety Limit Switches > Complete Push Type Switches



Representative Photo Only
(actual product may vary based on configuration selections)

Safety Limit Switch, 22mm Plastic, Roller Plunger, 1 N.C., 1 N.O., Snap Acting, M20 Conduit

- Factory sealed versions for demanding industrial environments
- Complete range of IEC style solutions for both safety and standard sensing applications
- Wide range of operating voltages and current ratings
- Extensive range of different housing styles and mounting options
- Wide variety of operating heads and levers

SPECIFICATIONS

Product Series	440P 22mm Plastic
Component Type Field Switching & Sensing	Limit Switch, Complete with Operator
Contact Configuration	1 NO + 1 NC
Contact Action	Slow Action action
Actuator Type	Top push roller plunger
Current Rating (AC 15 240Vac)G	3 A
Conduit Entry	M20 entry
Material, Body / Housing	Glass-Filled PBT / Valox material
Height	90 mm
Width	31 mm
Depth	31 mm
Operating Temperature, Max	70 °C max
Operating Temperature, Min	2 °C min
IP Rating	IP66
Standards Compliance	EN 1088 EN 60947-5-1 ANSI B11.19 EN 954 / ISO 13849:1999 Category 1 NFPA 79 AS/NZS 4024 Category 1
Certifications	CE C-UL-US

Catalogue No: **440P-CRPS11B**

LMT SW SAFETY 22mm PL ROLLER PLUNGER 1NC 1NO M20

Field Switching and Sensing > Limit Switches > Limit Switches > Allen-Bradley Limit Switches > Bulletin 440P IEC-Style Safety Limit Switches > Complete Push Type Switches



REFERENCES	
IECEX Certificate	-
Supplier Declaration of Conformity:	-
Installation Guide:	-
User Manual:	-
Manufacturer Datasheet:	-
Manufacturer Catalogue & Product Selection:	-

Typical Wiring Diagrams ©
Two-Circuit Type D4 4-Pin Micro Connector

Connector Pinout		1 N.C. + 1 N.O.	
		Terminal	Contact
	1	11	N.C.
	3	12	
	2	23	N.O.
	4	24	

Connection / Wiring Diagram