


Self-Lube bearing inserts complete with snap ring

1100CG Series

1100CG

With parallel outside diameter and integral set screw lock



Shaft diameter		RHP designation	Dimensions (mm)													ISO Load ratings		Rec. max. speed	Mass (approx.)
mm	inches	1100CG Series	D	D1	C	C1	C2	B	s	d1	f	M	r	r1	dynamic Cr newtons	static Cor newtons	rev/min	kg	
20		1120-20CG	47.000	52.68	15.88	2.39	4.17	31.00	12.73	28.30	1.12	5.00	1.00	0.50	12800	6650	6700	0.23	
	¾	1120-¾CG																	
25		1125-25CG	52.000	57.81	19.05	2.39	4.39	34.10	14.33	34.00	1.12	5.00	1.00	0.50	14000	7880	6250	0.31	
	⅞	1125-⅞CG																	
	1⅝	1125-1⅝CG																	
	1	1125-1CG																	
30		1130-30CG	62.000	67.69	22.22	3.18	5.10	38.10	15.93	40.30	1.70	5.00	1.00	0.50	19500	11300	5300	0.42	
	1⅛	1130-1⅛CG																	
	1⅜	1130-1⅜CG																	
35		1135-35CG	72.000	78.51	23.81	3.18	5.61	42.90	17.53	46.90	1.70	6.50	1.00	1.00	25700	15300	4500	0.61	
	1¼	1135-1¼CG																	
	1⅝	1135-1⅝CG																	
	1⅞	1135-1⅞CG																	
40		1140-40CG	80.000	86.51	27.78	3.18	6.22	49.20	19.03	52.40	1.70	8.00	1.00	1.00	32500	19900	4000	0.91	
	1½	1140-1½CG																	
45		1145-45CG	85.000	91.51	27.78	3.18	6.52	49.20	19.04	57.40	1.70	8.00	1.00	1.00	32500	20500	3700	1.05	
	1⅝	1145-1⅝CG																	
	1⅞	1145-1⅞CG																	
	1¾	1145-1¾CG																	
	1⅞	1150-1⅞CG	90.000	96.49	28.58	3.18	6.72	51.59	19.10	62.40	2.46	10.00	1.00	1.00	35000	23200	3400	1.10	
	1⅝	1150-1⅝CG																	
55		1155-55CG	100.000	106.50	30.16	3.18	7.43	55.60	22.20	68.90	2.46	10.00	1.00	1.00	43500	29200	3100	1.50	
	2	1155-2CG																	
	2⅜	1155-2⅜CG																	

Please check availability