

Data sheet for three-phase Squirrel-Cage-Motors SIMOTICS



Motor type: 1AV1063B

SIMOTICS GP - 63 M - IM B14 - 4p

Client order no.	Item-No	Offer no.
Order no.	Consignment no.	project

Remarks

Electrical data

Safe Area

U	Δ / Y	f	P	P	I	n	M	$\eta^{3)}$			$\cos\varphi^{3)}$			I_A/I_N	M_A/M_N	M_K/M_N	IE-CL
[V]		[Hz]	[kW]	[hp]	[A]	[1/min]	[Nm]	4/4	3/4	2/4	4/4	3/4	2/4	I_i/I_N	T_i/T_N	T_B/T_N	
230	Δ	50	0.18	-/-	1.12	1360	1.3	57.0	55.1	47.8	0.71	0.62	0.49	2.8	1.9	2.1	IE1
400	Y	50	0.18	-/-	0.64	1360	1.3	57.0	55.1	47.8	0.71	0.62	0.49	2.8	1.9	2.1	IE1
460	Y	60	0.21	-/-	0.59	1670	1.2	66.0	63.7	56.5	0.68	0.58	0.47	3.2	2.1	2.3	IE1
IM B14 / IM 3601		FS 63 M		kg		IP55		IEC/EN 60034		IEC, DIN, ISO, VDE, EN							

Environmental conditions : -20 °C - +40 °C / 1,000 m

Mechanical data

Sound level (SPL / SWL) at 50Hz 60Hz	/ dB(A) ²⁾	/ dB(A) ²⁾	Condensate drainage holes	No -/-
Moment of inertia	0.0004 kg m ²		External earthing terminal	No -/-
Bearing DE NDE	6201 2ZC3	6201 2ZC3	Vibration severity grade	A
bearing lifetime			Insulation	155(F) to 130(B)
L _{10mh} F _{Rad max} acc. catalogue 50 60Hz ¹⁾	20000 h	16000 h	Duty type	S1
L _{10mh} F _{Rad min} for coupling operation 50 60Hz ¹⁾	40000 h	32000 h	Direction of rotation	bidirectional
Lubricants	Unirex N3		Frame material	aluminum
Regreasing device	No		Coating (paint finish)	Standard paint finish C2
Grease nipple	-/-		Color, paint shade	RAL7030
Type of bearing	Preloaded bearing DE		Motor protection	(A) without (Standard)
			Method of cooling	IC411 - self ventilated, surface cooled

Terminal box

Terminal box position	top	Cable diameter from ... to ...	9.0 mm - 17.0 mm
Material of terminal box	Aluminium	Cable entry	-/-
Type of terminal box	TB1 B00	Cable gland	-/-
Contact screw thread	M4		
Max. cross-sectional area	1.5 mm ²		

Notes:

I_A/I_N = locked rotor current / current nominal
 M_A/M_N = locked rotor torque / torque nominal
 M_K/M_N = break down torque / nominal torque

1) L10mh according to DIN ISO 281 10/2010
2) at rated power / at full load

3) Value is valid only for DOL operation with motor design IC411

responsible dep.	technical reference	created by	approved by					
DI MC LVM		DT Configurator						
	document type			document status		customer		
	datasheet			released				
	title			document number				
	1LE1002-0BB32-2KA4							
© Siemens AG 2020				rev.	creation date	language	Page	
				01	2020-09-29 18:15	en	1/1	