


Slide Unit: Built-in Shock Absorber Ball Bushing Bearing Type

Series CXWL

ø10, ø16, ø20, ø25, ø32

How to Order



Applicable Auto Switch/Refer to pages 1719 to 1827 for further information on auto switches.

Type	Special function	Electrical entry	Indicator light	Wiring (Output)	Load voltage		Rail mounting		Applicable cylinder size		Lead wire length (m)*					Pre-wired connector		Applicable load	
					DC		AC	Perpendicular	In-line	Housing mounting	Plate mounting	0.5 (Nil)	3 (L)	5 (Z)	None (N)				
Solid state switch	—	Grommet	Yes	3-wire (NPN)	24 V	5 V, 12 V	F7NV	F79	ø16 ø20 ø25 ø32	ø10 ø16 ø20 ø25 ø32	●	●	○	—	○	IC circuit	Relay, PLC		
		3-wire (PNP)		F7PV			F7P	●			●	○	—	○					
	Diagnostic indication (2-color indication)	Connector		2-wire		12 V	F7BV	J79			●	●	○	—	○	—			
				3-wire (NPN)		5 V, 12 V	J79C	—			●	●	●	●	—				
				3-wire (PNP)			F7NWX	F79W			●	●	○	—	○	IC circuit			
				2-wire		12 V	—	F7PW			●	●	○	—	○				
				Water resistant (2-color indication)		Grommet	F7BWX	J79W			●	●	○	—	○	—			
							F7BAV	F7BA			—	●	○	—	○				
	With diagnostic output (2-color indication)	Grommet		4-wire (NPN)		5 V, 12 V	—	F79F			—	●	○	—	○	IC circuit			
				3-wire (NPN equivalent)		—	5 V	—			—	A76H	●	●	—			—	—
Reed switch	—	Grommet	Yes	2-wire	24 V	—	200 V	A72	A72H	ø16 ø20 ø25 ø32	ø10 ø16 ø20 ø25 ø32	●	●	—	—	—	IC circuit	Relay, PLC	
						—	12 V	100 V	A73			A73H	●	●	—	—			—
		Connector	No			5 V, 12 V	100 V or less	A80	A80H			●	●	—	—	—	IC circuit		
						12 V	—	A73C	—			●	●	●	●	—			—
						5 V, 12 V	24 V or less	A80C	—			●	●	●	●	—	IC circuit		
						3-wire (NPN equivalent)	—	5 V	—			—	E76A	ø10	—	●			●
		Grommet	No	2-wire	24 V	12 V	100 V	—	E73A	●	●	—	—			—			
						5 V, 12 V	100 V or less	—	E80A	●	●	—	—			—			

* Lead wire length symbols: 0.5 m Nil (Example) F79W
3 m L (Example) F79WL
5 m Z (Example) F79WZ
None N (Example) J79CW

* Solid state auto switches marked with "○" are produced upon receipt of order.
** It is impossible to mount solid state switches to the housing mounting ø10.

- Since there are other applicable auto switches than listed, refer to page 517 for details.
- For details about auto switches with pre-wired connector, refer to pages 1784 and 1785.

Series CXWL

Built-in shock absorber

This is built-in shock absorber style in which the shock absorber is enclosed in the housing.

Dramatically reduced installation labor

The machining precision required for positioning during the installation of the cylinder has been reduced through the adoption of a special pin hole machining process, thus decreasing the amount of labor involved in adjustment.

High-precision ball bushing

The bearings made of ball bushings decrease the rise in starting pressure that could be caused by a load imbalance.

This also enables smooth operation by ensuring stable travel resistance.

Provided with an end lock mechanism

An end lock is also available, which maintains the cylinder's original position even if the air supply is interrupted.



Made to Order Specifications
(For details, refer to pages 1851 to 2021.)

Symbol	Specifications
—XB11	Long stroke type
—XB13	Low speed cylinder (5 to 50 mm/s)
—XC22	Fluororubber seal
—X146	Hollow piston rod
—X138	Adjustable stroke
—X168	Helical insert thread
—X169	2 built-in magnets

Standard Stroke

Model	Standard stroke (mm)							
	25	50	75	100	125	150	175	200
CXWL10-□□	●	●	●	●	—	—	—	—
CXWL16-□□	●	●	●	●	●	●	●	●
CXWL20-□□	●	●	●	●	●	●	●	●
CXWL25-□□	●	●	●	●	●	●	●	●
CXWL32-□□	(*)	●	●	●	●	●	●	●

Note) The strokes marked with "(*)" has an absorber of single side plate mounting style.

Specifications

Type	Non-lube	
Fluid	Air	
Proof pressure	1.5 MPa	
Max. operating pressure	1.0 MPa	
Min. operating pressure	CXWL10/16	0.15 MPa
	CXWL20/25/32	0.10 MPa
Ambient & fluid temperature	-10 to 60°C (No freezing)	
Piston speed (Non-lube)	30 to 500 mm/s	
Cushion	Shock absorber	
Stroke adjustable range	Standard stroke: ±2 mm	
Accessory (Option)	Straight knock pin (2 pcs.), Adjusting bolt* (-X138)	

* "-X138" has a stroke adjustable range of -12.5 mm on one side.

Maximum Load Mass/Non-rotating Accuracy/Maximum Holding Force

Model	CXWL10	CXWL16	CXWL20	CXWL25	CXWL32
Max. movable mass ⁽¹⁾	1 kg	4 kg	5 kg	7 kg	10 kg
Non-rotating accuracy ⁽²⁾ (Deflection of a piston rod is not included.)	± 0.09°	± 0.03°	± 0.03°	± 0.02°	± 0.01°
Max. holding force (End lock model)	39.2 N	98.1 N	147.1 N	245.2 N	392.3 N

Note 1) Place the center of gravity of the load and center of the slide unit close during operation. If they are placed far apart from each other, please consult with SMC.

Note 2) The factors are obtained under the conditions of a 25 strokes plate is pushed out.

Shock Absorber Specifications

Shock absorber ⁽¹⁾		RB0805-X552	RB1006-X552	RB1411 RB1411-X552
Applicable slide unit		CXWL10/16-□□	CXWL20/25-□□	CXWL32-□□
Maximum energy absorption (J)		0.98	3.92	14.7
Stroke absorption (mm)		5	6	11
Max. collision speed (m/sec)		0.05 to 5		
Max. operating frequency (cycle/min) ⁽²⁾		80	70	45
Max. allowable thrust (N)		147	353	667
Ambient temperature range (°C)		-10 to 80		
Spring force (N)	Extended	1.96	4.22	6.86
	Retracted	3.83	6.18	15.30
Mass (g)		15	25	65

Note 1) "-X552" is an exclusive shock absorber installed in the housing, and is the screw not attached specification of the outer part of the outer tube. "CXWL32-25" is mounted on a single side of the plate and of the screw attached specification.

Note 2) It denotes the values at the maximum energy absorption per one cycle. Therefore, the operating frequency can be increased according to the energy absorption.

* The shock absorber service life is different from that of the cylinder depending on the operating conditions. Refer to the Series RB Specific Product Precautions for the replacement period.

Theoretical Output


(N)

Model	Rod size (mm)	Piston area (mm ²)	Operating pressure (MPa)							
			0.2	0.3	0.4	0.5	0.6	0.7	0.8	0.9
CXWL10-□□	6	101	20	30	40	51	61	71	81	91
CXWL16-□□	10	245	49	74	98	123	147	172	196	221
CXWL20-□□	12	402	80	121	161	201	241	281	322	362
CXWL25-□□	14	597	119	179	239	299	358	418	478	537
CXWL32-□□	20	980	196	294	392	490	588	686	784	882

Note) Theoretical output (N) = Pressure (MPa) x Piston area (mm²)

Slide Unit: Built-in Shock Absorber Ball Bushing Bearing Type **Series CXWL**

ø16 Basic Type: CXWL16- **Stroke/25 to 200**



Model	F	L	P	Q	S	SS	Z	ZZ
CXWL16-25	34.5	39	52	160	27	121	148	184
CXWL16-50	47	64	52	210	52	146	198	234
CXWL16-75	53	89	65	260	77	171	248	284
CXWL16-100	53	114	90	310	102	196	298	334
CXWL16-125	65.5	139	90	360	127	221	348	384
CXWL16-150	78	164	90	410	152	246	398	434
CXWL16-175	90.5	189	90	460	177	271	448	484
CXWL16-200	103	214	90	510	202	296	498	534

CX2

CXW

CXT

CXSJ

CXS

D-□

-X□

Individual
-X□