

Product information

99 11 250

High Leverage Concreters' Nipper

High lever transmission

DIN ISO 9242



- 25 % less effort required compared to conventional concreters' nippers of the same size
- Extra-slim form for tying deep mounted steel rods
- To lace concrete reinforcing steel with binding wire from a roll
- Wire is twisted and cut in a single pass
- High-leverage joint, minimising strain, even when thick binding wires are used
- The high damping of the cutting stroke on cutting through the binding wire reduces the strain on tendons and muscles
- Cutting edges additionally hardened; cutting edge hardness approx. 61 HRC
- High-grade special tool steel, forged, multi stage oil-hardened

General

| | |
|-----------------|--------------------|
| Article No. | 99 11 250 |
| EAN | 4003773071402 |
| Pliers | black atramentized |
| Head | polished |
| Handles | plastic coated |
| Weight | 429 g |
| Dimensions | 250 x 47 x 23 mm |
| Standard | DIN ISO 9242 |
| REACH compliant | no |
| RohS compliant | no |

Technical details

| | |
|--|-----------------|
| Cutting capacities hard wire (diameter) | Ø 1.8 mm |
| Cutting capacities medium hard wire (diameter) | Ø 3.3 mm |
| Cutting edge length mm | 23.0 mm 25.0 mm |

Classification

| | |
|----------------|------------|
| eCl@ss 5.1.4 | 21040301 |
| proficl@ss 6.0 | AAC483c003 |

technical change and errors excepted