




## UC209D1

**Set Screw Type** 

## **Product Information**



## **Included products**

| Bearing | UC209D | Bearing |
|---------|--------|---------|
|         | 1      |         |

## **Nominal Dimensions**

| d       | 45   | mm | Bore diameter       |
|---------|------|----|---------------------|
| D       | 85   | mm | Outside diameter    |
| B,B4    | 49.2 | mm | Width of inner ring |
| С       | 22   | mm | Outer ring width    |
| r(min.) | 1.5  | mm | Chamfer dimension   |





| <b>S</b> 1        | 30.2      | mm | Distance from locking device side face to raceway centre |
|-------------------|-----------|----|--|
| G                 | 8         | mm | Distance face to thread centre                           |
| ds                | M 8×1     |    | Set screw  |
| Ca                | 6.1       | mm | Distance from oil hole centre to raceway centre          |
| d4                | 57.5      | mm | Outside diameter of inner ring                           |
|                   |           |    |  |
| Basic Load Rating | <b>JS</b> |    |  |
| Cr                | 32.5      | kN | Basic dynamic load rating                                |
| C0r               | 20.4      | kN | Basic static load rating                                 |
|                   |           |    |  |
| Mass              |           |    |  |

Mass approx.

Mass approx.

0.68

kg