




Self-Lube® bearing inserts

1200EC and 1200ECG Series

1300EC Series

1200EC				1200ECG							1300EC				
With spherical outside diameter, non-re-greaseable outer ring and eccentric collar lock				With spherical outside diameter, re-greaseable outer ring and eccentric collar lock							With parallel outside diameter and eccentric collar lock				
															
Shaft diameter		RHP designation			Dimensions (mm)							ISO Load ratings		Rec. max. speed rev/min	Mass (approx.) kg
mm	inches	1200EC Series	1200ECG Series	1300EC Series	D	C	B ₂	s ₁	d ₂	r	dynamic C _r newtons	static C _{or} newtons			
12		1217-12EC	1217-12ECG	1317-12EC	40.000	12.00	28.63	6.53	28.60	0.60	9550	4800	7000	0.15	
15		1217-15EC	1217-15ECG	1317-15EC											
16		1217-16EC	1217-16ECG	1317-16EC											
17		1217-17EC	1217-17ECG	1317-17EC											
½		1217-½EC	1217-½ECG	1317-½EC											
⅝		1217-⅝EC	1217-⅝ECG	1317-⅝EC											
20		1220-20EC	1220-20ECG	1320-20EC	47.000	14.00	31.03	7.53	33.30	1.00	12800	6650	6700	0.16	
¾		1220-¾EC	1220-¾ECG	1320-¾EC											
25		1225-25EC	1225-25ECG	1325-25EC	52.000	15.00	31.03	7.53	38.10	1.00	14000	7880	6250	0.23	
⅞		1225-⅞EC	1225-⅞ECG	1325-⅞EC											
1⅝		1225-1⅝EC	1225-1⅝ECG	1325-1⅝EC											
1		1225-1EC	1225-1ECG	1325-1EC											
30		1230-30EC	1230-30ECG	1330-30EC	62.000	16.00	35.73	9.03	44.50	1.00	19500	11300	5300	0.40	
1⅞		1230-1⅞EC	1230-1⅞ECG	1330-1⅞EC											
1⅜		1230-1⅜EC	1230-1⅜ECG	1330-1⅜EC											
1¼		1230-1¼EC	1230-1¼ECG	1330-1¼EC											
35		1235-35EC	1235-35ECG	1335-35EC	72.000	17.00	38.93	9.53	55.60	1.00	25700	15300	4500	0.58	
1¼		1235-1¼EC	1235-1¼ECG	1335-1¼EC											
1⅝		1235-1⅝EC	1235-1⅝ECG	1335-1⅝EC											
1⅞		1235-1⅞EC	1235-1⅞ECG	1335-1⅞EC											
40		1240-40EC	1240-40ECG	1340-40EC	80.000	18.00	43.73	11.03	60.30	1.00	32500	19900	4000	0.73	
1½		1240-1½EC	1240-1½ECG	1340-1½EC											
45		1245-45EC	1245-45ECG	1345-45EC	85.000	19.00	43.73	11.04	63.50	1.00	32500	20500	3700	0.87	
1⅞		1245-1⅞EC	1245-1⅞ECG	1345-1⅞EC											
1⅞		1245-1⅞EC	1245-1⅞ECG	1345-1⅞EC											
1¾		1245-1¾EC	1245-1¾ECG	1345-1¾EC											
50		1250-50EC	1250-50ECG	1350-50EC	90.000	20.00	43.73	11.04	69.90	1.00	35000	23200	3400	0.98	
1⅞		1250-1⅞EC	1250-1⅞ECG	1350-1⅞EC											
1⅝		1250-1⅝EC	1250-1⅝ECG	1350-1⅝EC											
2		1250-2EC	1250-2ECG	1350-2EC											
55		1255-55ECG			100.000	21.00	48.40	12.04	76.20	1.50	43500	29200	3100	1.16	
2		1255-2ECG													

Please check availability