



**FAG****1210-K-TVH-C3** [🔗](#)

Self-aligning ball bearing

Self-aligning ball bearing 12..-K-TVH, tapered bore taper 1:12, plastic cage

Technical information



Main Dimensions & Performance Data

d	50 mm	Bore diameter
D	90 mm	Outside diameter
B	20 mm	Width
C _r	22.900 N	Basic dynamic load rating, radial
C _{0r}	8.100 N	Basic static load rating, radial
C _{ur}	520 N	Fatigue load limit, radial
n _G	8.700 1/min	Limiting speed
n _{gr}	7.700 1/min	Reference speed
≈m	0,506 kg	Weight

Mounting dimensions

d _{a min}	57 mm	Minimum diameter shaft shoulder
d _{a max}	62 mm	Maximum diameter shaft shoulder
D _{a max}	83 mm	Maximum diameter of housing shoulder
d _{b min}	53 mm	Minimum cavity diameter of the sleeve
B _{a min}	5 mm	Minimum cavity width of the sleeve
r _{a max}	1 mm	Maximum fillet radius

Dimensions

r _{min}	1,1 mm	Minimum chamfer dimension
D ₁	77,13 mm	Shoulder diameter outer ring
d ₁	62,7 mm	Shoulder diameter inner ring

Temperature range


T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



View product details on medias

13.11.2024, 12:36:42 IST

SCHAEFFLER



Calculation factors

e	0,2	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,15	Dynamic axial load factor
Y ₂	4,87	Dynamic axial load factor
Y ₀	3,3	Static axial load factor

Additional information

H210	Adapter sleeve
------	----------------