


## Sealing ring

### ► Aluminum



00127843



00108760

| Part No.          | G    | d    | D    | s   | Delivery quantity [Piece] | Working pressure min./max. [bar] | Ambient temperature min./max. [°C] |  |  |
|-------------------|------|------|------|-----|---------------------------|----------------------------------|------------------------------------|--|--|
| <b>1820209011</b> | M5   | 5.2  | 7.4  | 1   | 100                       | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209000</b> | G1/8 | 10.2 | 13.4 | 1   | 100                       | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209001</b> | G1/4 | 14.2 | 17.9 | 1.5 | 100                       | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209002</b> | G3/8 | 17.2 | 20.9 | 1.5 | 100                       | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209003</b> | G1/2 | 21.2 | 25.9 | 1.5 | 100                       | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209006</b> | G3/4 | 27.3 | 31.9 | 2   | 50                        | -0.95 / 15                       | -20 / +100                         |  |  |
| <b>1820209008</b> | G1   | 33.3 | 38.9 | 2   | 50                        | -0.95 / 15                       | -20 / +100                         |  |  |

Sealing ring, form A DIN 7603  
G = thread size