

Vacuum Pad/ Bowl Shape with Non-slip Feature

Bowl Shape

Ø 32, Ø 40, Ø 50, Ø 63, Ø 80, Ø 100

Bowl Bellows Shape

Ø 32, Ø 40, Ø 50, Ø 63, Ø 80, Ø 100

RoHS

Longer life (More than twice the life of urethane pads)

Pad material: **FS61** (Fluoro-based rubber) with excellent abrasion resistance
Reduced number of pad replacements

Non-slip special ribs

Diagonal ribs are radially arranged to secure the gripping force in all directions.

- Prevents workpiece slippage
- Secure adsorbing and transferring are possible.

Bowl shape with excellent flexibility

Curved workpieces can also be adsorbed.



Horizontal holding force: 387 N (Pad diameter Ø 100)*1

Suitable for high-temperature workpieces (200 °C)*1

*1 For details, refer to the specifications on pages 4 and 11.

Suitable for workpieces with oil film


As oil is ejected to the grooves between special ribs, the lateral slipping of workpiece can be suppressed even on a steel plate with oil film.



New Bowl bellows shape

The bowl shape can handle curved workpieces.

The pad follows the workpiece shape, making stable adsorption possible.




ZP3M Series

SMC

CAT.EUS100-147B-UK

Mesh filter (Option)



- Reduced suction of foreign matter into the vacuum pump and ejector
- Detachable
- Opening: 250 μm

Installation from below is possible.



Insert-molded pad to prevent the pad from falling out of the adapter


Bowl bellows shape

Discharge time maximum reduced by **40 %** during adsorption horizontal transfer

Transfer conditions


Pad diameter: $\varnothing 50$, Workpiece mass: 1.3 kg,
Supply pressure: -85 kPa , Acceleration/
Deceleration: 5 [G]

ZP3M (Bowl bellows shape)




Deflection **Small** Discharge time **0.18 s**

ZP3E (Bellows type)





Deflection **Large** Discharge time **0.30 s**

Relationship between the amplitude and time





Bowl Shape Variations

Type	Mounting	Vacuum inlet direction	Connection			Vacuum inlet		Page
			Type	Size		Size		
				Pad diameter: Ø 32 to Ø 50	Pad diameter: Ø 63 to Ø 100	Pad diameter: Ø 32 to Ø 50	Pad diameter: Ø 63 to Ø 100	
	Direct mounting	Vertical	Male thread	M10 x 1.0	M16 x 1.5	Use the connection thread.		
				G1/4				
			Female thread	M14 x 1.0				
				G1/4				
				G3/8				
			Square adapter	□31.8				
	Plate mounting	Vertical	Male thread	M18 x 1.5	M22 x 1.5	M5 x 0.8	Rc1/8	
		Lateral						

p. 4


Bowl Bellows Shape Variations

Type	Mounting	Vacuum inlet direction	Connection			Vacuum inlet		Page
			Type	Size		Size		
				Pad diameter: Ø 32 to Ø 50	Pad diameter: Ø 63 to Ø 100	Pad diameter: Ø 32 to Ø 50	Pad diameter: Ø 63 to Ø 100	
With adapter 	Direct mounting	Vertical	Male thread	M10 x 1.0	M16 x 1.5	Use the connection thread.		
				G1/4				
			Female thread	G1/4				
				G3/8				
			Square adapter	□31.8				
With buffer 	Plate mounting	Vertical	Male thread	M18 x 1.5	M22 x 1.5	M5 x 0.8	Rc1/8	
		Lateral						

p. 11

CONTENTS

Vacuum Pad/ Bowl Shape with Non-slip Feature *ZP3M Series*




• Bowl Shape with Non-slip Feature

How to Order	p. 4
Specifications	p. 4
Dimensions/Models	p. 5
Construction	p. 9
Mounting Bracket Assembly	p. 10

• Bowl Bellows Shape with Non-slip Feature

How to Order	p. 11
Specifications	p. 11
Dimensions/Models	p. 12
Construction	p. 16
Mounting Bracket Assembly	p. 17
Specific Product Precautions	p. 18

Vacuum Pad/ Bowl Shape with Non-slip Feature **ZP3M Series**



How to Order

With adapter

ZP3M - T 63 R FS - A16 - MF

With buffer

ZP3M - T 63 R FS JB 30 - MF

1 Bowl shape 2 Pad diameter 3 Material 4 Buffer stroke 5 Connection thread and type 6 Mesh filter

1 Vacuum inlet direction

T	Vertical
Y	Lateral

4 Buffer stroke

Stroke [mm]	Pad size
	All sizes
10	●
30	●
50	●

6 Mesh filter

—	None
MF	With mesh filter

Mesh filter unit

Part no.	Pad diameter	
	Ø 32 to Ø 50	Ø 63 to Ø 100
ZPMF-60-D13	●	—
ZPMF-60-D18	—	●

2 Pad diameter

32	Ø 32
40	Ø 40
50	Ø 50
63	Ø 63
80	Ø 80
100	Ø 100

3 Material

Symbol	Material	Colour
FS	FS61 (Fluoro-based rubber)	Green

5 Connection thread and type

Mounting	Type	Symbol	Size	Pad diameter	
				Ø 32 to Ø 50	Ø 63 to Ø 100
Direct mounting	Male thread	A10	M10 x 1.0	●	—
		A16	M16 x 1.5	—	●
		AG02	G1/4	●	●
	Female thread	B14	M14 x 1.0	●	●
		BG02	G1/4	●	●
		BG03	G3/8	●	●
	Square adapter	S32	□31.8	●	●

* The adapter and pad are adhered to each other and cannot be disassembled.

Specifications

Pad Material

Material	FS61 (Fluoro-based rubber)
Colour of rubber	Green
Rubber hardness (Shore A: ±5°)	65
Operating temperature range*1	0 °C to 200 °C
Ambient temperature	0 °C to 150 °C

*1 Surface temperature of the workpiece to be adsorbed

Adapter Specifications

Connection	Male thread		Female thread	Square adapter
Pad diameter	Ø 32 to Ø 50	Ø 63 to Ø 100	Ø 32 to Ø 100	Ø 32 to Ø 100
Size	M10 x 1.0 G1/4	M16 x 1.5 G1/4	M14 x 1.0 G1/4 G3/8	□31.8
Vacuum inlet	Use the connection thread and type.			

Buffer Specifications

Pad diameter		Ø 32 to Ø 50			Ø 63 to Ø 100		
Non-rotating specification		JB: Rotating, With bushing			JB: Rotating, With bushing		
Stroke [mm]		10	30	50	10	30	50
Connection thread		M18 x 1.5			M22 x 1.5		
Spring reactive force	At 0 stroke	5.0			10.0		
	At full stroke	6.5	8.5	10.5	11.5	13.5	15.5

Pad Specifications

Part no.	Horizontal holding force [N]*1		Minimum curvature radius for adsorption [mm]*2
	Without oil	With oil	
ZP3M-T32RFS	47	21	14
ZP3M-T40RFS	81	53	15
ZP3M-T50RFS	111	74	20
ZP3M-T63RFS	170	108	27.5
ZP3M-T80RFS	231	178	36
ZP3M-T100RFS	387	224	46

*1 These are actual measurement values when flat workpieces were adsorbed at a setting vacuum pressure of -60 kPa; however, they are not guaranteed values. (According to SMC's tests)


The values vary depending on the conditions (shape, surface roughness, oil type, oil amount, and other conditions) of the workpiece.

*2 These are actual measurement values when cylindrical workpieces were adsorbed at a setting vacuum pressure of -85 kPa; however, they are not guaranteed values. (According to SMC's tests)

Mesh Filter Specifications

Mesh filter	60
Opening	250 µm


Buffer assembly part no. p. 10



Model							A	B	B ^{±2}	C	D	E	F	G	H	J	K	st ^{±2}	Min. opening hole size of the adapter	Weight [g]
	Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Connection thread	④ Mesh filter														
ZP3M	T	32	R	FS	A10	— MF	32	33.2	38.3	M10 x 1.0	7	14.3	23.8	20	17	20.4	5	6	Ø 5	16.1
					AG02					G1/4	6.5		24.1	25	22					24.5
		40			A10		40	41.3	47.8	M10 x 1.0	7	17.8	27.3	20	17	21	5	8.4	Ø 5	17.3
					AG02					G1/4	6.5		27.6	25	22					25.7
		50			A10		50	51.6	58.6	M10 x 1.0	7	19.4	28.9	20	17	21.4	5	10.4	Ø 5	21.1
					AG02					G1/4	6.5		29.2	25	22					29.5
		63			A16		63.5	64.8	73.3	M16 x 1.5	9	24.1	36.1	27	24	32.4	8	12	Ø 8	47.1
					AG02					G1/4	6.5		35.6							46.7
		80			A16		80.6	81.8	92.2	M16 x 1.5	9	27.1	39.1	27	24	33	8	14.4	Ø 8	61.3
					AG02					G1/4	6.5		38.6							60.9
		100			A16		100	102.2	113.4	M16 x 1.5	9	33.9	45.9	27	24	34.4	8	20.1	Ø 8	96.7
					AG02					G1/4	6.5		45.4							100.4

*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.





Model							A	B	B ^{±2}	C	D	E	F	G	H	J	K	st ^{±2}	Min. opening hole size of the adapter	Weight [g]
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Connection thread	④ Mesh filter															
ZP3M	T	R	FS	B14 BG02 BG03 B14 BG02 BG03 B14 BG02 BG03 B14 BG02 BG03 B14 BG02 BG03	— MF	32	33.2	38.3	M14 x 1.0	8	14.3	31.6	23	19	20.4	5	6	Ø 5	20.9	
									G1/4	11		33.6	20	17					19.1	
									G3/8	11.4		34.1	26	22					26.3	
						40	41.3	47.8	M14 x 1.0	8	17.8	35.1	23	19	21	5	8.4	Ø 5	22.1	
									G1/4	11		37.1	20	17					20.3	
									G3/8	11.4		37.6	26	22					27.5	
						50	51.6	58.6	M14 x 1.0	8	19.4	36.7	23	19	21.4	5	10.4	Ø 5	25.9	
									G1/4	11		38.7	20	17					24.1	
									G3/8	11.4		39.2	26	22					31.3	
						63	64.8	73.3	M14 x 1.0	8	24.1	41.6	23	19	32.4	8	12	Ø 8	42.2	
									G1/4	11		42.6	22	19					42.5	
									G3/8	11.4		44.6	25	22					46.4	
						80	81.8	92.2	M14 x 1.0	8	27.1	44.6	23	19	33	8	14.4	Ø 8	56.4	
									G1/4	11		45.6	22	19					56.7	
									G3/8	11.4		47.6	25	22					60.5	
						100	102.2	113.4	M14 x 1.0	8	33.9	51.4	23	19	34.4	8	20.1	Ø 8	92.3	
									G1/4	11		52.4	22	19					92.6	
									G3/8	11.4		54.4	25	22					96.5	

*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

Dimensions/Models

With adapter Direct mounting type (Square adapter)



ZP3M - T **1** **63** **2** **R** **FS** **3** **- S32 - MF**




Model							A	B	B ^{*2}	C	D	E	st ^{*2}	Min. opening hole size of the adapter	Weight [g]
	Vacuum inlet direction	1 Pad diameter	Form	2 Material *1	Connection thread	3 Mesh filter									
ZP3M	T	32	R	FS	S32	- MF	32	33.2	38.3	14.3	26.3	20.4	6	Ø 5	26.1
		40					40	41.3	47.8	17.8	29.8	21	8.4	Ø 5	27.3
		50					50	51.6	58.6	19.4	31.4	21.4	10.4	Ø 5	31.1
		63					63.5	64.8	73.3	24.1	36.8	32.4	12	Ø 8	48.7
		80					80.6	81.8	92.2	27.1	39.8	33	14.4	Ø 8	62.8
		100					100	102.2	113.4	33.9	46.6	34.4	20.1	Ø 8	97.4

*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

Square adapter mounting groove dimensions (Recommended)




* For details on how to use the square adapter, refer to "Mounting" on page 18.

ZP3M Series

Dimensions/Models

With buffer Plate mounting type (Vacuum inlet direction: Vertical)



ZP3M - T 63 R FS JB 10 - MF

①

②

③


④

⑤

JB

Rotating, With bushing

Section Z (2:1)




Model								A	B	B ^{1*2}	C	D	E	F	H	J	K	L	M	N	P	Q	R	st*2	Min. opening hole size of the adapter	Weight [g]																			
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Buffer spec.	④ Buffer stroke	⑤ Mesh filter																																							
ZP3M	T	R	FS	JB	10	— MF	32	33.2	38.3	123.3	71.3	14.3	20.4	M18 x 1.5	5	19	11	35	27	14	17	16	8.4	Ø 3	205																				
					30					148.3	96.3														219.5																				
					50					168.3	116.3														231																				
					40		41.3	47.8	126.8	74.8	17.8	21	M22 x 1.5										8		28	8	50	30	17	24	24	14.4	Ø 4	206.2											
									30	151.8																								99.8	220.7										
									50	171.8																								119.8	232.2										
					50		51.6	58.6	128.4	76.4	19.4	21.4																				M22 x 1.5		8	28	8	50	30	17	24	24	14.4	Ø 4	210	
									30	153.4																																		101.4	224.5
									50	173.4																																		121.4	236
					63		64.8	73.3	164.1	94.1	24.1	32.4		M22 x 1.5	8	28	8	50	30	17	24	24		14.4																		Ø 4		355	
									30	189.1																																		119.1	383.8
									50	209.1																																		139.1	406.7
					80		81.8	92.2	167.1	97.1	27.1	33	M22 x 1.5										8	28	8	50	30	17	24	24	14.4		Ø 4											369.2	
									30	192.1																																		122.1	397.9
									50	212.1																																		142.1	420.9
					100		102.2	113.4	173.9	103.9	33.9	34.4																			M22 x 1.5	8		28	8	50	30	17	24	24	14.4		Ø 4	404.6	
									30	198.9																																		128.9	433.4
									50	218.9																																		148.9	456.3

*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

Dimensions/Models

With buffer Plate mounting type (Vacuum inlet direction: Lateral)



Model							A	B	B*±2	C	D	E	F	G	H	J	K	L	M	N	P	Q	R	S	T	U	st*±2	Min. opening hole size of the adapter	Weight [g]													
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Buffer spec.	④ Buffer stroke	⑤ Mesh filter																																				
ZP3M	Y	R	FS	JB	10	— MF	32	33.2	38.3	118.3	74.3	14.3	20.4	33.7	M18 x 1.5	5	19	11	35	27	14	17	16	M5 x 0.8	5	8.5	6	Ø 5	203.2													
					30					143.3	99.3																		219.1													
					50					163.3	119.3																		231.6													
					40		41.3	47.8	121.8	77.8	17.8	21	37.2	M18 x 1.5													5		19	11	35	27	14	17	16	M5 x 0.8	5	8.5	8.4	204.4		
									30	146.8																															102.8	220.3
									50	166.8																															122.8	232.8
					50		51.6	58.6	123.4	79.4	19.4	21.4	38.8	M18 x 1.5													5		19	11	35	27	14	17	16	M5 x 0.8	5	8.5	10.4	208.2		
									30	148.4																															104.4	224.1
									50	168.4																															124.4	236.6
					63		64.8	73.3	161.1	101.1	24.1	32.4	50.6	M18 x 1.5													5		19	11	35	27	14	17	16	M5 x 0.8	5	8.5	12	209.1		
									30	186.1																															126.1	386.8
									50	206.1																															146.1	411.7
					80		81.8	92.2	164.1	104.1	27.1	33	53.6	M22 x 1.5													8		28	8	50	30	17	24	24	Rc1/8	—	12.5	14.4	210.9		
									30	189.1																															129.1	400.9
									50	209.1																															149.1	425.9
					100		102.2	113.4	170.9	110.9	33.9	34.4	60.4	M22 x 1.5													8		28	8	50	30	17	24	24	Rc1/8	—	12.5	14.4	20.1		
30	195.9	135.9	436.4																																							
50	215.9	155.9	461.3																																							

*1 FS: FS61 (Fluoro-based rubber)


*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

ZP3M Series

Construction

With adapter

ZP3M-T□RFS-A□ ZP3M-T□RFS-B□ ZP3M-T□RFS-S32



Component Parts


No.	Description	Material
1	Pad	FS61 (Fluoro-based rubber)
2	Insert adapter	Aluminium alloy
3	Adapter	Aluminium alloy (Anodised)
4	O-ring	FKM
5	Mesh filter	Stainless steel

* The parts 1, 2, and 3 are adhered to each other and cannot be disassembled.

With buffer

ZP3M-T□RFSJB□-□

ZP3M-Y□RFSJB□-□



Component Parts

No.	Description	Material
1	Pad	FS61 (Fluoro-based rubber)
2	Insert adapter	Aluminium alloy
3	Adapter	Aluminium alloy (Anodised)
4	O-ring	FKM
5	Mesh filter	Stainless steel
6	Adapter	Aluminium alloy (Anodised)
7	Piston rod	Structural steel (Hard chrome plating)
8	Return spring	Stainless steel
9	Buffer body	Brass (Electroless nickel plating)
10	Buffer adapter	Brass (Electroless nickel plating)
11	Nut	Steel (Zinc chromated) M18 x 1.5 Structural steel (Nickel plating) M22 x 1.5
12	Bushing	—

* The parts 1, 2, and 3 are adhered to each other and cannot be disassembled.

Replacement Parts: Mesh Filter Unit

Part no.	Pad diameter	
	Ø 32 to Ø 50	Ø 63 to Ø 100
ZPMF-60-D13	●	—
ZPMF-60-D18	—	●



ZP3M Series

Mounting Bracket Assembly

Product part no.	<p>ZP3M - (T/Y) ① R FS JB ② - □</p> <p>T: Vertical vacuum inlet Y: Lateral vacuum inlet</p> <p>Pad diameter</p> <p>Mesh filter</p> <p>Buffer stroke</p> <p>Pad material</p>	
Component parts	<p>ZP3M-T□RFSJB□-□</p> <p>③ Mounting nut</p> <p>① Buffer assembly (Vacuum inlet: Vertical) (With mounting nut)</p> <p>② Pad with adapter</p>	<p>ZP3M-Y□RFSJB□-□</p> <p>③ Mounting nut</p> <p>① Buffer assembly (Vacuum inlet: Lateral) (With mounting nut)</p> <p>② Pad with adapter</p>

		Symbol	① Pad diameter					
			32	40	50	63	80	100
① Buffer assembly (With mounting nut)	② Buffer stroke	10	ZP3EB-(T/Y)1JB②			ZP3EB-(T/Y)2JB②		
		30						
		50						
② Pad with adapter	M10 x 1.0		ZP3M-T32RFS-A10-□	ZP3M-T40RFS-A10-□	ZP3M-T50RFS-A10-□	—		
	M16 x 1.5		—			ZP3M-T63RFS-A16-□	ZP3M-T80RFS-A16-□	ZP3M-T100RFS-A16-□
③ Mounting nut (Single unit)	M18 x 1.5		ZPNA-M18			—		
	M22 x 1.5		—			ZPNA-M22		

[Buffer assembly part number example]


Product part no. **ZP3M - T63RFS JB 10**

Buffer assembly **ZP3EB - T2 JB 10**

② Buffer stroke

Vacuum Pad/ Bowl Bellows Shape with Non-slip Feature

ZP3M Series



How to Order

With adapter

ZP3M-T 63 RB FS

- A16 - MF

With buffer

ZP3M-T 63 RB FS JB 30

- MF

Bowl bellows shape

With buffer

1 Vacuum inlet direction

T	Vertical
Y	Lateral

4 Buffer stroke

Stroke [mm]	Pad size
	All sizes
10	●
30	●
50	●

6 Mesh filter

-	None
MF	With mesh filter

Mesh filter unit

Part no.	Pad diameter	
	Ø 32 to Ø 50	Ø 63 to Ø 100
ZPMF-60-D13	●	-
ZPMF-60-D18	-	●

2 Pad diameter

32	Ø 32
40	Ø 40
50	Ø 50
63	Ø 63
80	Ø 80
100	Ø 100

3 Material

Symbol	Material	Colour
FS	FS61 (Fluoro-based rubber)	Green

5 Connection thread and type

Mounting	Type	Symbol	Size	Pad diameter	
				Ø 32 to Ø 50	Ø 63 to Ø 100
Direct mounting	Male thread	A10	M10 x 1.0	●	-
		A16	M16 x 1.5	-	●
	Female thread	AG02	G1/4	●	●
		BG02	G1/4	●	●
	Square adapter	S32	□31.8	●	●

* The adapter and pad are adhered to each other and cannot be disassembled.

Specifications

Pad Material

Material	FS61 (Fluoro-based rubber)
Colour of rubber	Green
Rubber hardness (Shore A: ±5°)	65
Operating temperature range*1	0 °C to 200 °C
Ambient temperature	0 °C to 150 °C

*1 Surface temperature of the workpiece to be adsorbed

Adapter Specifications

Connection	Male thread		Female thread	Square adapter
Pad diameter	Ø 50	Ø 63, Ø 80	Ø 32 to Ø 100	Ø 32 to Ø 100
Size	M10 x 1.0 G1/4	M16 x 1.5 G1/4	G1/4 G3/8	□31.8
Vacuum inlet	Use the connection thread and type.			

Buffer Specifications

Pad diameter	Ø 32 to Ø 50			Ø 63 to Ø 100		
Non-rotating specification	JB: Rotating, With bushing			JB: Rotating, With bushing		
Stroke [mm]	10	30	50	10	30	50
Connection thread	M18 x 1.5			M22 x 1.5		
Spring reactive force	At 0 stroke	5.0		10.0		
	At full stroke	6.5	8.5	10.5	11.5	13.5

Pad Specifications

Part no.	Horizontal holding force [N]*1		Minimum curvature radius for adsorption [mm]*2
	Without oil	With oil	
ZP3M-T32RBFS	35.8	18.0	12.5
ZP3M-T40RBFS	37.5	25.2	17.5
ZP3M-T50RBFS	63	46	27.5
ZP3M-T63RBFS	86	59	27.5
ZP3M-T80RBFS	122	91	34
ZP3M-T100RBFS	184.1	149.1	60

*1 These are actual measurement values when flat workpieces were adsorbed at a setting vacuum pressure of -60 kPa; however, they are not guaranteed values. (According to SMC's tests)

The values vary depending on the conditions (shape, surface roughness, oil type, oil amount, and other conditions) of the workpiece.

*2 These are actual measurement values when cylindrical workpieces were adsorbed at a setting vacuum pressure of -85 kPa; however, they are not guaranteed values. (According to SMC's tests)


Mesh Filter Specifications

Mesh filter	60
Opening	250 µm

Buffer assembly part no. p. 17

Dimensions/Models

With adapter Direct mounting type (Male thread)



ZP3M - T 63 RB FS - A16 - MF

1

2

4

3



		Pad diameter [mm]	
		Ø 32 to Ø 50	Ø 63 to Ø 100
A10	M10 x 1.0	○	—
A16	M16 x 1.5	—	○
AG02	G1/4	○	○

Model							A	B	B*※2	C	D	E	F	G	H	J	st※2	Min. opening hole size of the adapter	Weight [g]
	Vacuum inlet direction	① Pad diameter	Form	② Material ※1	③ Connection thread	④ Mesh filter													
ZP3M	T	32	RB	FS	A10	— MF	32	34	34.9	M10 x 1.0	7	19	28	22	19	5	9	Ø 5	29.9
					AG02					G1/4	6.5							Ø 6	31.7
		40			A10		40	41.8	43.9	M10 x 1.0	7	19.8	28.8				10	Ø 5	31.4
					AG02					G1/4	6.5							Ø 6	33.1
		50			A10		50	52.4	55.6	M10 x 1.0	7	24.9	36.9	30	27	8	11.8	Ø 5	68.6
					AG02					G1/4	6.5							70.3	
		63			A16		63	65.4	69.5	M16 x 1.5	9	29.3	41.3				15.2	Ø 6	86.3
					AG02					G1/4	6.5								80.1
		80			A16		80	82.6	87.5	M16 x 1.5	9	37.9	49.9				22.1		119.3
					AG02					G1/4	6.5								113.1
		100			A16		100	103	107.1	M16 x 1.5	9	44.6	56.6				25.8		166.5
					AG02					G1/4	6.5								160.4

※1 FS: FS61 (Fluoro-based rubber)

※2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

ZP3M Series

Dimensions/Models

With adapter Direct mounting type (Female thread)


ZP3M - T **63** RB **FS** - **BG02** - **MF**

①

②

④

③




Connection thread: BG02

BG02	G1/4
BG03	G3/8

Ø 32, Ø 40


Ø 50 to Ø 100



Connection thread: BG03

Ø 32, Ø 40

Ø 50 to Ø 100



Model							A	B	B* ²	C	D	E	F	G	st* ²	Min. opening hole size of the adapter	Weight [g]
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Connection thread	④ Mesh filter												
ZP3M	T	RB	FS	BG02	MF	32	34	34.9	G1/4	11.0	19	28.0	44.0	5	9	Ø 5	17.5
				BG03					G3/8	11.4							33.5
				BG02		40	41.8	43.9	G1/4	11.0	19.8	28.8	44.8	5	10	Ø 5	19.0
				BG03					G3/8	11.4							34.9
				BG02		50	52.4	55.6	G1/4	12.5	24.9	41.9	36.9	8	11.8	Ø 8	69.1
				BG03					G3/8	11.4							46.4
				BG02		63	65.4	59.5	G1/4	12.5	29.3	46.3	41.3	8	15.2	Ø 8	78.8
				BG03					G3/8	11.4							55.9
				BG02		80	82.6	87.5	G1/4	12.5	37.9	54.9	49.9	8	22.1	Ø 8	111.9
				BG03					G3/8	11.4							89.0
				BG02		100	103	107.1	G1/4	12.5	44.6	61.6	56.6	8	25.8	Ø 8	159.1
				BG03					G3/8	11.4							136.2



*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

ZP3M Series

Dimensions/Models

With adapter Direct mounting type (Square adapter)




ZP3M - T **63** RB **FS** - S32 - **MF**

①

②

③




	Vacuum inlet direction	Model					A	B	B* ²	C	D	st* ²	Min. opening hole size of the adapter	Weight [g]
		① Pad diameter	Form	② Material * ¹	Connection thread	③ Mesh filter								
ZP3M	T	32	RB	FS	S32	MF	32	34	34.9	19	31.2	9	Ø 5	30.2
		40					40	41.8	43.9	19.8	32	10		31.6
		50					50	52.4	55.6	24.9	36.6	11.8		50.0
		63					63	65.4	69.5	29.3	41	15.2	Ø 8	59.8
		80					80	82.6	87.5	37.9	49.6	22.1		92.8
		100					100	103	107.1	44.6	56.3	25.8		140.0

*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.


Square adapter mounting groove dimensions (Recommended)



* For details on how to use the square adapter, refer to "Mounting" on page 18.


Dimensions/Models

With buffer Plate mounting type (Vacuum inlet direction: Vertical)



Buffer assembly

Section Z (5:1)



Pad with adapter

ZP3M - T 63 RB FS JB 10 - MF

1

2

3

4

5

JB

Rotating, With bushing

Model								A	B	B*2	C	D	E	G	H	J	K	L	M	U	V	st*2	Min. opening hole size	Weight [g]					
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Buffer spec.	④ Buffer stroke	⑤ Mesh filter																							
ZP3M	T	32	RB	FS	JB	10	— MF	32	34	34.9	127.5	75.5	19									9	Ø 3	221.0					
						30					152.5	100.5												235.5					
						50					172.5	120.5												246.9					
		40				40		41.8	43.9	10	40	41.8	43.9	128.3	76.3	19.8	35	11	14	27	M18 x 1.5	16	19	5	10	Ø 3	222.4		
										30				153.3	101.3												236.9		
										50				173.3	121.3												248.3		
		50				50		52.4	55.6	10	50	52.4	55.6	136.4	84.4	24.9										11.8	Ø 3	259.7	
										30				161.4	109.4													274.2	
										50				181.4	129.4													285.6	
		63				63		65.4	69.5	10	63	65.4	69.5	169.3	99.3	29.3											15.2	Ø 4	399.1
										30				194.3	124.3														427.9
										50				214.3	144.3														450.8
		80				80		82.6	87.5	10	80	82.6	87.5	177.9	107.9	37.9	50	8	17	30	M22 x 1.5	24	27	8	22.1	Ø 4		432.2	
										30				202.9	132.9													460.9	
										50				222.9	152.9													483.9	
		100				100				10	100	103	107.1	184.6	114.6	44.6											25.8		479.4
										30				209.6	139.6														508.2
										50				229.6	159.6														531.1


*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.

ZP3M Series

Dimensions/Models

With buffer Plate mounting type (Vacuum inlet direction: Lateral)



Model							A	B	B'±2	C	D	E	F	G	H	J	K	L	N	P	R	S	T	U	V	st±2	Min. opening hole size	Weight [g]
Vacuum inlet direction	① Pad diameter	Form	② Material *1	③ Buffer spec.	④ Buffer stroke	⑤ Mesh filter																						
ZP3M	Y	RB	FS	JB	10	MF	32	34	34.9	122.5	78.5	19	37.9													9	Ø 5	219.4
					30					147.5	103.5																	235.2
					50					167.5	123.5																	247.8
					10		40	41.8	43.9	123.3	79.3	19.8	38.7	35	11	14	27	M18 x 1.5	M5 x 0.8	5	16	19	8.5	19	5	10		220.8
					30					148.3	104.3																	236.7
					50					168.3	124.3																	249.2
					10		50	52.4	55.6	131.4	87.4	24.9	46.8													11.8		258.0
					30					156.4	112.4																	273.9
					50					176.4	132.4																	286.5
					10		63	65.4	69.5	166.3	106.3	29.3	55.8													15.2		400.3
					30					191.3	131.3																	431.5
					50					211.3	151.3																	456.4
					10		80	82.6	87.5	174.9	114.9	37.9	64.4	50	8	17	30	M22 x 1.5	Rc1/8	—	24	28	12.5	27	8	22.1	Ø 6	433.3
					30					199.9	139.9																	464.5
					50					219.9	159.9																	489.4
					10		100	103	107	181.6	121.6	44.6	71.1													25.8		480.6
					30					206.6	146.6																	511.8
					50					226.6	166.6																	536.7


*1 FS: FS61 (Fluoro-based rubber)

*2 B': Maximum pad diameter at the time of adsorption, st: The stroke is a guide value at the setting vacuum pressure of -90 kPa.


Construction

With adapter


ZP3M-T□RBFS-A□




ZP3M-T (32, 40)
RBFS-BG02




ZP3M-T (32, 40)
RBFS-BG03




ZP3M-T□RBFS-S32



ZP3M-T(50, 63, 80, 100)
RBFS-BG02



ZP3M-T(50, 63, 80, 100)
RBFS-BG03




Component Parts

No.	Description	Material	Note
1	Pad	FS61 (Fluoro-based rubber)	—
2	Insert adapter	Aluminium alloy	
3	Adapter	Structural carbon steel (Electroless nickel plating)	ZP3M-T (32, 40) RBFS-A□
		Aluminium alloy (Anodised)	ZP3M-T (50, 63, 80, 100) RBFS-A□, BG02
4	O-ring	FKM	—
5	Mesh filter	Stainless steel	


* The parts 1, 2, and 3 are adhered to each other and cannot be disassembled.

With buffer

ZP3M-T□RBFSJB□-□



ZP3M-Y□RBFSJB□-□



Component Parts

No.	Description	Material	Note
1	Pad	FS61 (Fluoro-based rubber)	—
2	Insert adapter	Aluminium alloy	
3	Adapter	Structural carbon steel (Electroless nickel plating)	
4	O-ring	FKM	
5	Mesh filter	Stainless steel	
6	Adapter	Aluminium alloy (Anodised)	
7	Piston rod	Structural steel (Hard chrome plating)	
8	Return spring	Stainless steel	
9	Buffer body	Brass (Electroless nickel plating)	
10	Buffer adapter	Brass (Electroless nickel plating)	
11	Nut	Steel (Zinc chromated) M18 x 1.5	
		Structural steel (Nickel plating) M22 x 1.5	
12	Bushing	—	

* The parts 1, 2, and 3 are adhered to each other and cannot be disassembled.



Replacement Parts: Mesh Filter Unit

Part no.	Pad diameter	
	Ø 32 to Ø 50	Ø 63 to Ø 100
ZPMF-60-D13	●	—
ZPMF-60-D18	—	●



ZP3M Series

Mounting Bracket Assembly

Product part no.	<p>ZP3M - (T/Y) ① RB FS JB ② - □</p> <p>T: Vertical vacuum inlet Y: Lateral vacuum inlet</p> <p>Pad diameter</p> <p>Mesh filter</p> <p>Buffer stroke</p> <p>Pad material</p>	
Component parts	<div> <p>ZP3M-T□RBFSJB□-□</p>  <p>③ Mounting nut</p> <p>① Buffer assembly (Vacuum inlet: Vertical) (With mounting nut)</p> <p>② Pad with adapter</p> </div> <div> <p>ZP3M-Y□RBFSJB□-□</p>  <p>③ Mounting nut</p> <p>① Buffer assembly (Vacuum inlet: Lateral) (With mounting nut)</p> <p>② Pad with adapter</p> </div>	

		Symbol	① Pad diameter					
			32	40	50	63	80	100
① Buffer assembly (With mounting nut)	② Buffer stroke	10	ZP3EB-(T/Y)1JB②			ZP3EB-(T/Y)2JB②		
		30						
		50						
② Pad with adapter	M10 x 1.0		ZP3M-T32RBFS-A10-□	ZP3M-T40RBFS-A10-□	ZP3M-T50RBFS-A10-□	—		
	M16 x 1.5		—			ZP3M-T63RBFS-A16-□	ZP3M-T80RBFS-A16-□	ZP3M-T100RBFS-A16-□
③ Mounting nut (Single unit)	M18 x 1.5		ZPNA-M18			—		
	M22 x 1.5		—			ZPNA-M22		

[Buffer assembly part number example]

Product part no. **ZP3M - T63RBFS JB 10**

Buffer assembly **ZP3EB - T2 JB 10**

② Buffer stroke



ZP3M Series

Vacuum Pad/Specific Product Precautions

Be sure to read this before handling the products. Refer to the back cover for safety instructions. For vacuum equipment precautions, refer to the “Handling Precautions for SMC Products” and the “Operation Manual” on the SMC website: <https://www.smc.eu>

Design

- Before use, please check the transfer conditions with the customer's actual equipment.**
The transfer ability varies depending on the workpiece material, the friction between the pad and workpiece, moment, wind, vibration, etc. Testing with the customer's actual equipment is necessary.
- In cases where the workpieces are heavy or dangerous objects, etc., take measures to address a possible loss of adsorption force (installation of a drop prevention guide, etc.).**
- The oil, chemical, and other substances adhered to the workpiece may not be suitable for the pad material.**
Before using this product, sufficiently verify the workpieces in your operating environment.

Mounting

- When mounting the product, tighten with the tightening torque shown in the table below.**
If excessive or insufficient tightening torque is applied, sealing failure or loose screws may result.
When using a product equipped with a buffer, if the buffer is tightened to a torque beyond the appropriate tightening torque range, the buffer may malfunction.

With Adapter (Male thread type)

Model	Connection thread size	Proper tightening torque [N·m]
ZP3M-T□(R,RB)FS-A10-□	M10 x 1.0	8 to 10
ZP3M-T□(R,RB)FS-A16-□	M16 x 1.5	13 to 15
ZP3M-T□(R,RB)FS-AG02-□	G1/4	8 to 12

With Adapter (Female thread type)


Model	Connection thread size	Proper tightening torque [N·m]
ZP3M-T□RFS-B14-□	M14 x 1.0	11 to 13
ZP3M-T□(R,RB)FS-BG02-□	G1/4	8 to 12
ZP3M-T□(R,RB)FS-BG03-□	G3/8	15 to 20

With Buffer

Model	Connection thread size	Proper tightening torque [N·m]
ZP3M-(T/Y)□(R,RB)FSJB□-□	M18 x 1.5	28 to 32
	M22 x 1.5	45 to 50

2. How to use the square adapter

Use the square adapter by inserting it to an attachment you prepare. If it is difficult to insert the square adapter, apply grease to the O-ring. Prepare retaining measures by yourself.






Handling

- Depending on the type of oil or foreign matter, the mesh filter may be clogged at an early stage.**
Before using this product, sufficiently verify the mesh filter in your operating environment.
- Periodically inspect the mesh filter.**
An adsorbing malfunction may be caused by the clogging of the mesh filter.
- When the vacuum pad is pressed, make sure it stays within the stroke range.**
If this product is used with a stroke exceeding the maximum stroke, the pad may be broken or may reach the end of its service life earlier.
- Vacuum pads are consumable. Please replace them when cracks or deformation is confirmed during periodic maintenance.**
- The workpiece size must be equal to or greater than the minimum curvature radius for adsorption.**
If the workpiece size is smaller than the minimum curvature radius for adsorption, an adsorbing malfunction may occur.
- As the adapter and pad are adhered to each other, they cannot be disassembled.**
- When adsorbing a plane, the pad skirt may be entrained depending on the workpiece with rough friction surface. Before using this product, sufficiently verify the adsorbing condition.**

Safety Instructions

These safety instructions are intended to prevent hazardous situations and/or equipment damage. These instructions indicate the level of potential hazard with the labels of “Caution,” “Warning” or “Danger.” They are all important notes for safety and must be followed in addition to International Standards (ISO/IEC)¹⁾, and other safety regulations.

-  **Danger:** **Danger** indicates a hazard with a high level of risk which, if not avoided, will result in death or serious injury.
-  **Warning:** **Warning** indicates a hazard with a medium level of risk which, if not avoided, could result in death or serious injury.
-  **Caution:** **Caution** indicates a hazard with a low level of risk which, if not avoided, could result in minor or moderate injury.

- 1) ISO 4414: Pneumatic fluid power – General rules and safety requirements for systems and their components.
ISO 4413: Hydraulic fluid power – General rules and safety requirements for systems and their components.
IEC 60204-1: Safety of machinery – Electrical equipment of machines. (Part 1: General requirements)
ISO 10218-1: Robots and robotic devices – Safety requirements for industrial robots – Part 1: Robots.
etc.

Warning

1. The compatibility of the product is the responsibility of the person who designs the equipment or decides its specifications.

Since the product specified here is used under various operating conditions, its compatibility with specific equipment must be decided by the person who designs the equipment or decides its specifications based on necessary analysis and test results. The expected performance and safety assurance of the equipment will be the responsibility of the person who has determined its compatibility with the product. This person should also continuously review all specifications of the product referring to its latest catalogue information, with a view to giving due consideration to any possibility of equipment failure when configuring the equipment.

2. Only personnel with appropriate training should operate machinery and equipment.

The product specified here may become unsafe if handled incorrectly. The assembly, operation and maintenance of machines or equipment including our products must be performed by an operator who is appropriately trained and experienced.

3. Do not service or attempt to remove product and machinery/equipment until safety is confirmed.

1. The inspection and maintenance of machinery/equipment should only be performed after measures to prevent falling or runaway of the driven objects have been confirmed.
2. When the product is to be removed, confirm that the safety measures as mentioned above are implemented and the power from any appropriate source is cut, and read and understand the specific product precautions of all relevant products carefully.
3. Before machinery/equipment is restarted, take measures to prevent unexpected operation and malfunction.

4. Our products cannot be used beyond their specifications. Our products are not developed, designed, and manufactured to be used under the following conditions or environments.

Use under such conditions or environments is not covered.

1. Conditions and environments outside of the given specifications, or use outdoors or in a place exposed to direct sunlight.
2. Use for nuclear power, railways, aviation, space equipment, ships, vehicles, military application, equipment affecting human life, body, and property, fuel equipment, entertainment equipment, emergency shut-off circuits, press clutches, brake circuits, safety equipment, etc., and use for applications that do not conform to standard specifications such as catalogues and operation manuals.
3. Use for interlock circuits, except for use with double interlock such as installing a mechanical protection function in case of failure. Please periodically inspect the product to confirm that the product is operating properly.

Caution

We develop, design, and manufacture our products to be used for automatic control equipment, and provide them for peaceful use in manufacturing industries.

Use in non-manufacturing industries is not covered.

Products we manufacture and sell cannot be used for the purpose of transactions or certification specified in the Measurement Act.

The new Measurement Act prohibits use of any unit other than SI units in Japan.

Limited warranty and Disclaimer/Compliance Requirements

The product used is subject to the following “Limited warranty and Disclaimer” and “Compliance Requirements”. Read and accept them before using the product.

Limited warranty and Disclaimer

1. The warranty period of the product is 1 year in service or 1.5 years after the product is delivered, whichever is first.²⁾ Also, the product may have specified durability, running distance or replacement parts. Please consult your nearest sales branch.
2. For any failure or damage reported within the warranty period which is clearly our responsibility, a replacement product or necessary parts will be provided. This limited warranty applies only to our product independently, and not to any other damage incurred due to the failure of the product.
3. Prior to using SMC products, please read and understand the warranty terms and disclaimers noted in the specified catalogue for the particular products.
- 2) Vacuum pads are excluded from this 1 year warranty.
A vacuum pad is a consumable part, so it is warranted for a year after it is delivered. Also, even within the warranty period, the wear of a product due to the use of the vacuum pad or failure due to the deterioration of rubber material are not covered by the limited warranty.

Compliance Requirements

1. The use of SMC products with production equipment for the manufacture of weapons of mass destruction (WMD) or any other weapon is strictly prohibited.
2. The exports of SMC products or technology from one country to another are governed by the relevant security laws and regulations of the countries involved in the transaction. Prior to the shipment of a SMC product to another country, assure that all local rules governing that export are known and followed.

Safety Instructions

Be sure to read “Handling Precautions for SMC Products” (M-E03-3) before using.

Revision History

Edition B	- Bowl bellows shape: Ø 50, Ø 63, and Ø 80 have been added. - The number of pages has been increased from 12 to 20.	BZ
------------------	--	----

SMC Corporation (Europe)

Austria	+43 (0)2262622800	www.smc.at	office@smc.at
Belgium	+32 (0)33551464	www.smc.be	info@smc.be
Bulgaria	+359 (0)2807670	www.smc.bg	office@smc.bg
Croatia	+385 (0)13707288	www.smc.hr	office@smc.hr
Czech Republic	+420 541424611	www.smc.cz	office@smc.cz
Denmark	+45 70252900	www.smc.dk.com	smc@smcdk.com
Estonia	+372 651 0370	www.smcee.ee	info@smcee.ee
Finland	+358 207513513	www.smc.fi	smcfr@smc.fi
France	+33 (0)164761000	www.smc-france.fr	supportclient@smc-france.fr
Germany	+49 (0)61034020	www.smc.de	info@smc.de
Greece	+30 210 2717265	www.smchellas.gr	sales@smchellas.gr
Hungary	+36 23513000	www.smc.hu	office@smc.hu
Ireland	+353 (0)14039000	www.smcautomation.ie	sales@smcautomation.ie
Italy	+39 03990691	www.smcitalia.it	mailbox@smcitalia.it
Latvia	+371 67817700	www.smc.lv	info@smc.lv

Lithuania	+370 5 2308118	www.smc.lt	info@smc.lt
Netherlands	+31 (0)205318888	www.smc.nl	info@smc.nl
Norway	+47 67129020	www.smc-norge.no	post@smc-norge.no
Poland	+48 222119600	www.smc.pl	sales@smc.pl
Portugal	+351 214724500	www.smc.eu	apoioclientept@smc.smces.es
Romania	+40 213205111	www.smcromania.ro	smcromania@smcromania.ro
Russia	+7 (812)3036600	www.smc.eu	sales@smcru.com
Slovakia	+421 (0)413213212	www.smc.sk	office@smc.sk
Slovenia	+386 (0)73885412	www.smc.si	office@smc.si
Spain	+34 945184100	www.smc.eu	post@smc.smces.es
Sweden	+46 (0)86031240	www.smc.nu	smc@smc.nu
Switzerland	+41 (0)523963131	www.smc.ch	info@smc.ch
Turkey	+90 212 489 0 440	www.smcturkey.com.tr	info@smcturkey.com.tr
UK	+44 (0)845 121 5122	www.smc.uk	sales@smc.uk

South Africa	+27 10 900 1233	www.smcza.co.za	zasales@smcza.co.za
---------------------	-----------------	-----------------	---------------------