

Male Branch Tee: KQ2T




Applicable tubing O.D. (mm)	Connection thread Uni One-touch fittings	Model	H (width across flats)	⁽¹⁾ øD1	øD2	L1	L2	A*	M	Effective area (mm ²)		Mass (g)
										Nylon	Urethane	
4	1/8	KQ2T04-U01	10	10.4	10	18	20	21.5	16	6.0	6.0	9
	1/4	KQ2T04-U02	14				22					15
6	1/8	KQ2T06-U01	10	12.8	10	20	21.5	23.5	17	13.9	13.9	11
	1/4	KQ2T06-U02	14				23					17
	3/8	KQ2T06-U03	17				24					26
	1/2	KQ2T06-U04	22				25.5					31
8	1/8	KQ2T08-U01	12	15.2	12	23	22.5	26	18.5	26.3	18.2	15
	1/4	KQ2T08-U02	14				24.5					20
	3/8	KQ2T08-U03	17				25.5					28
	1/2	KQ2T08-U04	22				27					31
10	1/8	KQ2T10-U01	10	18.5	17	26.5	25	29.5	21	35.2	25	30
	1/4	KQ2T10-U02	14				26.5					27
	3/8	KQ2T10-U03	17				27					31
	1/2	KQ2T10-U04	22				30					51
12	1/4	KQ2T12-U02	17	20.9	17	28.5	27	31.5	22	57.2	45.2	31
	3/8	KQ2T12-U03	17				28					34
	1/2	KQ2T12-U04	22				31					54
	1/2	KQ2T12-U04	22				31					54
16	3/8	KQ2T16-U03	22	26.5	21	33	33	40.5	24	71	(71)	62
	1/2	KQ2T16-U04	22				35					63

* Reference dimensions after Uni thread installation.

Note 1) øD1: Max. diameter

Note 2) Dimensions in () are the case of soft nylon tubing.



K□

M□

H□

KK

D□

MS

LQ

MQR

T□

Male Run Tee: KQ2Y



Applicable tubing O.D. (mm)	Connection thread Uni One-touch fittings	Model	H (width across flats)	⁽¹⁾ øD1	øD2	L1	L2	A*	M	Effective area (mm ²)		Mass (g)
										Nylon	Urethane	
4	1/8	KQ2Y04-U01	10	10.4	10	18	20	34	16	6.4	6.4	9
	1/4	KQ2Y04-U02	14				22					15
6	1/8	KQ2Y06-U01	10	12.8	10	20	21.5	37.5	17	13.4	13.4	11
	1/4	KQ2Y06-U02	14				23					17
	3/8	KQ2Y06-U03	17				24					26
	1/2	KQ2Y06-U04	22				25.5					31
8	1/8	KQ2Y08-U01	12	15.2	12	23	22.5	41.5	18.5	25.6	17.7	15
	1/4	KQ2Y08-U02	14				24.5					19
	3/8	KQ2Y08-U03	17				25.5					28
	1/2	KQ2Y08-U04	22				27					31
10	1/8	KQ2Y10-U01	10	18.5	17	26.5	25	46.5	21	40.0	28.4	30
	1/4	KQ2Y10-U02	14				26.5					27
	3/8	KQ2Y10-U03	17				27					31
	1/2	KQ2Y10-U04	22				30					51
12	1/4	KQ2Y12-U02	17	20.9	17	28.5	27	49.5	22	57.4	45.4	31
	3/8	KQ2Y12-U03	17				28					35
	1/2	KQ2Y12-U04	22				31					55
	1/2	KQ2Y12-U04	22				31					55
16	3/8	KQ2Y16-U03	22	26.5	21	33	40.5	66	24	81	(81)	61
	1/2	KQ2Y16-U04	22				63					62

* Reference dimensions after Uni thread installation.

Note 1) øD1: Max. diameter

Note 2) Dimensions in () are the case of soft nylon tubing.

