Kits and Accessories

Suppressor and LED Indicators for PS1E

Mount between Solenoid Valve and the Interface Module





Circuit Diagram

PS1F1620

Characteristics	Voltage	Part Number	Weight	
			lb	kg
	24 VDC and 50/60 Hz	P8V-CR26C	.022	0.010
Indication by LED	48 VDC and 50/60 Hz	P8V-CR26D	.022	0.010
Sold in Lots of 5	115 V / 50 Hz 120 V / 60 Hz	P8V-CR24F	.028	0.012
	230 V / 50 Hz 240 V / 60 Hz	P8V-CR24J	.028	0.012

Marking Accessories

To be used in place of Write-On Marking Tabs



Clip-On Marker Strips	Part Number	
Strip of 10 Identical Numerals (State the Number required)	AB1-R•	
Strip of 10 Identical Letters (State the Letter required)	AB1-G•	
Strip of 10 - Signs*	AB1-R13	

^{*}Sold in Lots of 25 Strips of 10 Markers

Spare Parts

Description	Part Number	
1 lot of 100 O-ring Seals Between Modules (Pressure - Exhaust)	PPR-L12	
1 lot of 50 Seals Between Modules 3/2 or 4/2 and Coil PS1-E23 - 25 Seals (Type A) for Modules 3/2 and 4/2 Bistable	PPR-L13	
- 25 Seals (Type B) for Modules 4/2 Monostable and Bistable		

