

**FAG****1218-K-TVH-C3** [🔗](#)

Self-aligning ball bearing

Self-aligning ball bearing 12..-K-TVH, tapered bore taper 1:12, plastic cage

Technical information



Main Dimensions & Performance Data

d	90 mm	Bore diameter
D	160 mm	Outside diameter
B	30 mm	Width
C _r	57.000 N	Basic dynamic load rating, radial
C _{0r}	23.500 N	Basic static load rating, radial
C _{ur}	1.330 N	Fatigue load limit, radial
n _G	4.550 1/min	Limiting speed
n _{gr}	4.850 1/min	Reference speed
≈m	2,48 kg	Weight

Mounting dimensions


d _{a min}	101 mm	Minimum diameter shaft shoulder
d _{a max}	110 mm	Maximum diameter shaft shoulder
D _{a max}	149 mm	Maximum diameter of housing shoulder
d _{b min}	95 mm	Minimum cavity diameter of the sleeve
B _{a min}	7 mm	Minimum cavity width of the sleeve
r _{a max}	2 mm	Maximum fillet radius

Dimensions

r _{min}	2 mm	Minimum chamfer dimension
D ₁	138,7 mm	Shoulder diameter outer ring
d ₁	112,7 mm	Shoulder diameter inner ring

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



Calculation factors

e	0,17	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	3,74	Dynamic axial load factor
Y ₂	5,79	Dynamic axial load factor
Y ₀	3,92	Static axial load factor

Additional information

H218	Adapter sleeve
------	----------------