111mm Complete Set

111mm Plug Set

111mm Plug x 1

111mm Plugs - pack of 10

127mm Complete Set

127mm Plug Set

127mm Plug x 1

SBC - Solid Board Cutters & Accessories

☐ГПРЕБ 🚾 SBC - Solid Board Cutter Part Numbers & Technical Information

Part Number

SBC111SET

SBC PLUGSET

RPSBC111PLUG

SBC111PLUGX10

SBC127SET

SBC127PLUGSET

RPSBC127PLUG

SBC127PLUGX10

Contents

1xHexagon Drive Adaptor for SBC Cutter 1xSDS Plus Drive Adaptor for SBC Cutter

1x111mm Cobalt Solid Board Cutter

1x111mm Cobalt Solid Board Cutter

1x127mm Cobalt Solid Board Cutter

1x127mm Cobalt Solid Board Cutter

1xHexagon Drive Adaptor for SBC Cutter

1xSDS Plus Drive Adaptor for SBC Cutter

3x111mm Plugs

3x111mm Plugs

3x127mm Plugs

3x127mm Plugs

COBALT

Perfect for

Drill easy fix access holes in solid boards in under a minute



Available in 111mm & 127mm



111mm



A Depth Stop Ring

Precision manufactured depth-stop ring set to the same depth as the cap rebate makes it impossible to over-drill meaning the cap lies flush to the floor for a neat finish with 100% accuracy

Rebating Cutters

Hardened steel rebating cutters produce a 6.5mm(1/4") rebate in the floor material creating a ledge for the SBC caps to precisely locate on in the flooring

Cobalt Cutting Teeth

Tougher tooth design manufactured with M42 superior steel featuring 8% Cobalt provides excellent wear resistance properties at higher drilling temperatures. This gives extended tool life, and lasts at least 100% longer than standard bi-metallic holesaws

SBC can be used in:

up to 22mm thick

SBC is ideal when creating holes for:

- · Running cables under floors for
- installation or maintenance
- · Access when running pipework
- General work where access to the floor void under solid flooring is required

KNOW? SBC caps are

YOU

removable allowing for repeat access into solid floors

Flooring grade chip board

- rewires / installations
- · Access above downlighters during
- under flooring

Operation Speed Chart

127mm Plugs - pack of 10

Diameter Size mm	Recommended RPM	
111mm	900	
127mm	900	



SBC can be used with standard holesaw adaptors with a 5/8" - 18 UNF thread. Try the Hex Shank (part no. CHD32-64HEX) or the SDS Plus Shank (part no. CHD32-64SDS). See page 80.



Scan me for demo video



When using in waterproof boards, if it is required to maintain the waterproof integrity of the board, it is advisable to seal around the edges of the rebated cap with silicone sealant or similar

TECH TIP!





When used adaptor adaptor

