


# Plug socket with cable KMV-1-24DC-2,5-LED

Part number: 30939

**FESTO**



## Data sheet

| Feature                                    | Value                                       |
|--------------------------------------------|---------------------------------------------|
| Type code                                  | KMV                                         |
| Switching status indication                | LED                                         |
| Type of mounting                           | On air solenoid valve with M3 central screw |
| Product weight                             | 170 g                                       |
| Electrical connection                      | Form B<br>Socket                            |
| Nominal operating voltage DC               | 24 V                                        |
| Reverse polarity protection                | for all electrical connections              |
| Protective earth connection                | Available                                   |
| Cable length                               | 2.5 m                                       |
| Cable diameter                             | 6 mm                                        |
| Cable design                               | 3 x 0.75 mm <sup>2</sup>                    |
| Degree of protection                       | IP67<br>as per IEC 60529                    |
| Ambient temperature                        | -20 °C ... 80 °C                            |
| CE marking (see declaration of conformity) | As per EU RoHS directive                    |
| Corrosion resistance class (CRC)           | 1 - Low corrosion stress                    |
| Material of cable sheath                   | PVC                                         |
| Housing material                           | PC                                          |
| Material of pin contacts                   | Bronze                                      |
| Mounting position                          | Any                                         |