

Ball valve
VZBC-32-FF-40-22-F0405-V4V4T
Part number: 1692202

FESTO



Data sheet

Feature	Value
Type code	VZBC
Design	2-way ball valve
Actuation type	Mechanical
Sealing principle	Soft
Mounting position	Any
Type of mounting	Line installation
Fitting connection	Ring housing with threaded flange
Switching position indication	Slot direction = flow direction
Flange hole pattern	F05 F04
Inside diameter	32 mm
Nominal width DN	32
Valve function	2/2

Feature	Value
Manual override	None
Flow direction	Reversible
Nominal pressure of fitting PN	40
Actuating torque	24 Nm
Based on norm	ISO 5211 EN 1092-1
Symbol	00991458
Medium	Compressed air as per ISO 8573-1:2010 [:::] Neutral liquids Inert gas Water – no water vapor Other flow media on request
Temperature of medium	-10 °C ... 200 °C
Flow rate Kv	105 m³/h
Note on materials	Contains paint-wetting impairment substances RoHS-compliant
Housing material	High-alloy stainless steel
Material number of housing	1.4408
Seals material	PTFE-reinforced PTFE
Ball material	High-alloy stainless steel
Material number for ball	1.4408
Shaft material	High-alloy stainless steel
Material number for shaft	1.4401
Product weight	3700 g
CE marking (see declaration of conformity)	as per EU pressure equipment directive
Corrosion resistance class (CRC)	3 - High corrosion stress
Explosion prevention and protection	Zone 22 (ATEX) Zone 2 (ATEX) Zone 21 (ATEX) Zone 1 (ATEX)