

Product Data Sheet

Professional CFM/CMM Thermo-Anemometer

Product Features

- Air velocity, air flow and air temperature measurements
- · User selectable units: m/s, Km/h, MPH, Knots, ft/min
- MAX/MIN/Data hold
- Large backlit LCD
- · Low battery indicator
- Auto power off
- · Supplied in heavy duty carry case
- Available with 3 point Calibration Certificate traceable to National Standards, on request (order part number: 49/700/0)



Air Velocity Range: 0.3 to 45.0 m/s, 1.0 to 162 km/s

59 to 8858 ft/min, 0.5 to 87.5 knots

0.6 to 100.6 Mph

Temperature Range: -30 to 60°C (22 to 140°F)

Operating Conditions: -20 to 60°C < 90%RH (non-condensing)

Storage Conditions: -30 to 70°C < 75%RH

Air Velocity Accuracy: 3% +/- 0.1 **Air Velocity Resolution:** 0.1m/s

Temperature Accuracy: +/-1.5°C (+/-2.7°F)

Sampling Rate: 1 per second

Area Set: 0.001 to 9999m² (0.001 to 9999ft²)

Battery: 1 x 9V (included)

CE & RoHS/WEEE: Compliant

Hazard Information (SDS): See www.brannan.co.uk for information

LCD Dimensions: 55 x 45mm

Product Dimensions: Packaged: 290 x 355 x 90mm

Unpackaged: 185 x 66 x 33mm

Product Gross Weight: Packaged: 1404g

Component Weights: Meter: 332g

Case: 868g Box: 204g





Description	Barcode	Product No
Professional CFM/CMM Thermo-Anemometer	5 011405 134608	13/460/0

PDS 0252:16:R3

Please note: all information on this data sheet is correct at the time of printing, but our policy is one of continuous product development. We reserve the right to change specification without notice.

