




Technical datasheet

4T-LM12749/LM12710

Single row tapered roller bearings

Tapered roller bearing, pressed steel cage

Visual(s)



Product definition

d	21.99 mm
D	45.24 mm
B	16.64 mm
C	12.06 mm
T	15.49 mm
d1	34 mm
a	10.1 mm
rs min	1.3 mm
r1s min	1.3 mm
e	0.31
Y2	1.96
Y0	1.08
Mass	0.12 kg
Brand	NTN

Product performance

Dynamic load, C	29.6 kN
Rating life coefficient, A2	1.4
Static load, C0	34 kN
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.42 Hz
Characteristic rolling element frequency, BSF	6.18 Hz
Characteristic outer ring frequency, BPF0	7.18 Hz
Characteristic inner ring frequency, BPF1	9.82 Hz

Abutment dimensions

ra max	1.3 mm
r1a max	1.3 mm

Calculation factors

Equivalent dynamic radial load

$$P = X.F_r + Y.F_a$$

Fa / Fr ≤ e		Fa / Fr > e	
X	Y	X	Y
1	0	0.4	Y2

Equivalent static radial load

$$P_0 = X_0.F_r + Y_0.F_a$$

X ₀	Y ₀
0.5	Y0

If $P_0 < F_r$, then use $P_0 = F_r$

The values for e, Y2 and Y0 are shown in the above table