

## "HIGH STRENGTH" ROUND SLING

### Description

To use this sling is to combine the basic principles of quality and safety for a greater satisfaction. . Extra reinforced sheath for increased durability and better maintenance. . The wear indicators are yarns woven under the frame, in different colors from the sheath, all throughout the length of the sling, with an interval of 4 mm. . . Maximum load of use in tonne Standard: EN 1492-2 – Working factor 1:7



### Strong points

Better resistance to wear and abrasion, piercing and tearing. Individual traceability of each product (delivered with a certificate of conformity) Maximum use load in tonne

### Characteristics

| Ref.   | EAN           | Safe working load SWL<br>kg | Capacity length<br>m | Colour |
|--------|---------------|-----------------------------|----------------------|--------|
| 132900 | 3660338006500 | 1000                        | 1                    | Lilac  |
| 133000 | 3660338006517 | 1000                        | 1,5                  | Lilac  |
| 133100 | 3660338006524 | 1000                        | 2                    | Lilac  |
| 133200 | 3660338006623 | 2000                        | 1                    | Green  |
| 133300 | 3660338006630 | 2000                        | 1,5                  | Green  |
| 133400 | 3660338006647 | 2000                        | 2                    | Green  |
| 608052 | 3660338006548 | 1000                        | 3                    | Lilac  |
| 608056 | 3660338006661 | 2000                        | 3                    | Green  |
| 608059 | 3660338006746 | 3000                        | 1                    | Yellow |
| 608061 | 3660338006760 | 3000                        | 2                    | Yellow |
| 608063 | 3660338006784 | 3000                        | 3                    | Yellow |
| 608065 | 3660338006807 | 3000                        | 4                    | Yellow |