



Features & Benefits

Manufactured to BS7609 (1992) Standards.
Bell mouth cable entry terminals to ensure easy entry.
Electro tinned. Copper Conductivity to 99.9% I.A.C.S.
Maximum operating temperature: 149°C.

code	description	cable size	stud size	pack quantity
630101	CT1.5M4	1.5	4	100
630102	CT1.5M5	1.5	5	100
630201	CT2.5M4	2.5	4	100
630202	CT2.5M5	2.5	5	100
630203	CT2.5M6	2.5	6	100
630301	CT4M4	4	4	100
630302	CT4M5	4	5	100
630303	CT4M6	4	6	100
630401	CT6M4	6	4	100
630402	CT6M5	6	5	100
630403	CT6M6	6	6	100
630404	CT6M8	6	8	100
630405	CT6M10	6	10	100
630502	CT10M5	10	5	100
630503	CT10M6	10	6	100
630504	CT10M8	10	8	100
630505	CT10M10	10	10	100
630506	CT10M12	10	12	100
630602	CT16M5	16	5	100
630603	CT16M6	16	6	100
630604	CT16M8	16	8	100
630605	CT16M10	16	10	100
630606	CT16M11	16	12	100
630703	CT25M6	25	6	100
630704	CT25M8	25	8	100
630705	CT25M10	25	10	100
630706	CT25M12	25	12	100
630803	CT35M6	35	6	100
630804	CT35M8	35	8	100
630805	CT35M10	35	10	100
630806	CT35M12	35	12	100
630807	CT35M14	35	14	100
630903	CT50M6	50	6	50
630904	CT50M8	50	8	50
630905	CT50M10	50	10	50
630906	CT50M12	50	12	50
630907	CT50M14	50	14	50
630908	CT50M16	50	16	50

code	description	cable size	stud size	pack quantity
631003	CT70M6	70	6	10
631004	CT70M8	70	8	10
631005	CT70M10	70	10	10
631006	CT70M12	70	12	10
631007	CT70M14	70	14	10
631008	CT70M16	70	16	10
631009	CT70M20	70	20	10
631104	CT95M8	95	8	10
631105	CT95M10	95	10	10
631106	CT95M12	95	12	10
631107	CT95M14	95	14	10
631108	CT95M16	95	16	10
631109	CT95M20	95	20	10
631204	CT120M8	120	8	5
631205	CT120M10	120	10	5
631206	CT120M12	120	12	5
631207	CT120M14	120	14	5
631208	CT120M16	120	16	5
631209	CT120M20	120	20	5
631305	CT150M10	150	10	5
631306	CT150M12	150	12	5
631307	CT150M14	150	14	5
631308	CT150M16	150	16	5
631309	CT150M20	150	20	5
631405	CT185M10	185	10	5
631406	CT185M12	185	12	5
631407	CT185M14	185	14	5
631408	CT185M16	185	16	5
631409	CT185M20	185	20	5
631505	CT240M10	240	10	1
631506	CT240M12	240	12	1
631507	CT240M14	240	14	1
631508	CT240M16	240	16	1
631605	CT300M10	300	10	1
631606	CT300M12	300	12	1
631608	CT300M16	300	16	1
631706	CT400M12	400	12	1/1