

The Timken Company


4500 Mt Pleasant St. NW N. Canton, OH 44720

Phone: (234) 262-3000

E-Mail: <u>CustomerCAD@timken.com</u> • Web site: <u>www.timken.com</u>

Part Number UCFL317, UCFL 300 Two-Bolt Flanged Mounted Bearings - Set Screw Locking






<u>Specifications</u> | <u>Dimensions</u> | <u>Basic Load Ratings</u>


Specifications –				
Bearing Number UC31	7			
Shaft Size d 85 mr				
Locking Style Set So	rew Locking			
Housing Construction Two-E	olt Flange			

Dimensions -					
	Totallonath	370 mm			
	Total Length H	3/0111111			
	Total Height L	220 mm			
	Housing Width A	74 mm			
	Bolt Hole Spacing J	300 mm			
	olt Hole Size N	38 mm			

Flange Thickness A1	32 mm
Center of Bearing from Housing End A2	44 mm
Inner Ring Width B	96 mm
Center of Bearing from Bearing End S	40 mm
Dimension A0	100 mm
Bolt Size	M33

Basic Load Ratings		-
Static Load Rating	96800 N	
Dynamic Load Rating	133000 N	





Bearing Number	UC317			
Load Ratings - C _r	29900	lbf	133000	N
Load Ratings - C _{0r}	21762	lbf	96800	N
Weight	35.3	lb	16	kg
Bolt Size	M33			

THE TIMKEN COMPANY
NORTH CANTON, OHIO USA

UCFL317

UCFL 300 Two-Bolt Flanged Mounted Bearings - Set Screw Locking

Every reasonable effort has been made to ensure the accuracy of the information contained in this writing, but no liability is accepted for errors, omissions or for any other reason.

FOR DISCUSSION ONLY