

tesa® 4329 PV1



Product Information

Finely creped paper mask tape

The product is thin and flexible and, therefore, suitable for all general masking applications, as well as oven drying applications up to a temperature of 70 °C.

Features

The product is thin and flexible and, therefore, suitable for all general masking applications, as well as oven drying applications up to a temperature of 70 °C.

Main Application

- Masking
- Lacquering work
- Good flexibility for curves
- Can be used on painted metal, rubber, glass and chrome parts

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	slightly-creped paper	• Elongation at break	10 %
• Total thickness	125 µm	• Tensile strength	33 N/cm
• Type of adhesive	natural rubber	• Temperature resistance	70 °C

Adhesion to

- | | |
|---------|----------|
| • steel | 2.8 N/cm |
|---------|----------|

Properties

• Hand tearability	●●●●	• Sharp color edge	●●●●
• Easy to remove	Yes	• Conformability	●●●●
• Paint anchorage	●●●●		

Evaluation across relevant tesa® assortment: ●●●● very good ●●● good ●● medium ● low

tesa® 4329 PV1

Product Information



Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04329>