



ADA132U

RCBO Electronic 1M 1P 10kA B-32A 30mA A Class

Technical Characteristics

Architecture

Neutral position	right
Number of poles	1 P
Type of pole	1 P
Fixing mode	DIN rail type O (symmetrical)
Curve	B

Main electrical features

Rated operational voltage U _e	230 / 240 V
Frequency	50 Hz
Rated current	32 A

Voltage

Rated insulation voltage	250 V
Max operating voltage	253 V
Rated impulse withstand voltage	4000 V

Electric current

Rated residual operating current	30 mA
Rated short circuit breaking capacity I _{cn} under 230V AC according IEC60898-1	10 kA

Electric current / temperature

Rating current 30°C	32 A
---------------------	------

Dimensions

Depth of installed product	70 mm
Height of installed product	115 mm
Width of installed product	17.5 mm

Power

Total power loss under I _N	9.63 W
---------------------------------------	--------

Endurance

Electric endurance in number of cycles	2000
Number of mechanical operations	2000

Capacity

Number of modules	1
-------------------	---

Installation, mounting

Tightening torque	2,1Nm
-------------------	-------

Connection

Type of connection	with screw
--------------------	------------

Standards

Standard text	EN 61009-1 IEC 61009-1
---------------	---------------------------

European directive WEEE	concerned
Safety	
Protection index IP	IP20
Residual current type	A