

HOW TO ORDER

NVSA 4 **1** **2** 4 - **00** **A** **M**

Type of Actuation

- 1 = Single Pilot Spring Return
- 2 = Double Pilot Detented
- 3 = Double Pilot Spring Centered (All ports blocked in neutral)
- 4 = Double Pilot Spring Centered (Cylinder ports open to dual supply in neutral)
- 5 = Double Pilot Spring Offset

Valve Size

- 1 = Class 1
- 2 = Class 2
- 3 = Class 3
- 4 = Class 4

Options

- M = Interface Speed Control
- V1 = Red Pilot Indicator
- V2 = Green Pilot Indicator

Features

- A = Recessed non-locking operator, pilot pressure access through base of valve.
- B = No operator—Pilot pressure access through base of valve.
- C = Tapped junction box cover, pilot connections in junction box, but no operator.
- J = Tapped junction box cover, pilot connections in junction box, recessed non-locking operator.
- N = Blank junction box cover, recessed non-locking operator.
- O = Blank junction box cover, no operator.

Porting

- 00 = Indicates valve unit only. No base
 (Includes subplate gasket and hold down bolts.)

NVSA 4 24

- 01 = Mounted on Individual Subplate - 1/4" NPTF Side Ports (5)
- 51 = Mounted on Individual Subplate - 1/4" NPTF Side Ports (5); 10-32 Pilot Ports (4)
- 02 = Mounted on Individual Subplate - 3/8" NPTF Side Ports (5)
- 52 = Mounted on Individual Subplate - 3/8" NPTF Side Ports (5); 10-32 Pilot Ports (4)
- 03 = Mounted on Individual Subplate - 1/4" NPTF Bottom Ports (5)
- 06 = Mounted on Individual Subplate - 1/4" NPTF Side Supply (1); Bottom Ports (5)
- 21 = Mounted on Stacking Manifold Block - 3/8" NPTF Side Ports (4)
- 23 = Mounted on Stacking Manifold Block - 3/8" NPTF Side Ports (4); Bottom Ports (2)
- 28 = Mounted on Stacking Manifold Block - 3/8" Side Ports (6); Bottom Ports (5)
- 41 = Mounted on Stacking Manifold Block - 1/2" NPTF Side Ports (4)

NVSA 4 34

- 01 = Mounted on Individual Subplate - 3/8" NPTF Side Ports (5)
- 02 = Mounted on Individual Subplate - 1/2" NPTF Side Ports (5)
- 52 = Mounted on Individual Subplate - 1/2" NPTF Side Ports (5); 10-32 Pilot Ports (4)
- 03 = Mounted on Individual Subplate - 3/8" NPTF Side Ports (5); Bottom Ports (5)
- 31 = Mounted on Stacking Manifold Block - 3/8" NPTF Side Ports (4)
- 33 = Mounted on Stacking Manifold Block - 3/8" NPTF Side Ports (4); Bottom Ports (2)
- 38 = Mounted on Stacking Manifold Block - 3/8" NPTF Side Ports (6); Bottom Ports (5)
- 51 = Mounted on Stacking Manifold Block - 1/2" NPTF Side Ports (4)

NVSA 4 44

- 01 = Mounted on Individual Subplate - 1/2" NPTF Side Ports (5)
- 02 = Mounted on Individual Subplate - 3/4" NPTF Side Ports (5)
- 03 = Mounted on Individual Subplate - 1/2" NPTF Side Ports (5); Bottom Ports (5)
- 04 = Mounted on Individual Subplate - 3/4" NPTF Side Ports (5); Bottom Ports (5)
- 05 = Mounted on Individual Subplate - 1" NPTF Side Ports (5)
- 06 = Mounted on Individual Subplate - 3/4" NPTF Side Ports (5)