


# Service unit combination LFR-1/2-D-DI-MAXI-KG

Part number: 192446

**FESTO**



 [General operating condition](#)

## Data sheet

| Feature                                               | Value                                                                                                                |
|-------------------------------------------------------|----------------------------------------------------------------------------------------------------------------------|
| Size                                                  | Maxi                                                                                                                 |
| Series                                                | D                                                                                                                    |
| Actuator lock                                         | Rotary knob with detent                                                                                              |
| Mounting position                                     | Vertical +/-5°                                                                                                       |
| Grade of filtration                                   | 40 µm                                                                                                                |
| Condensate drain                                      | Manually rotating                                                                                                    |
| Design                                                | Branching module<br>Pressure switch<br>On/off valve<br>Filter regulator with pressure gauge<br>Safety start-up valve |
| Max. condensate volume                                | 43 ml                                                                                                                |
| Bowl guard                                            | Metal bowl guard                                                                                                     |
| Symbol                                                | 00991759                                                                                                             |
| Pressure gauge (ANALOG) or Pressure display (DIGITAL) | With pressure gauge                                                                                                  |
| Operating pressure                                    | 3 bar ... 16 bar                                                                                                     |
| Pressure regulation range                             | 2.5 bar ... 12 bar                                                                                                   |
| Operating medium                                      | Compressed air to ISO 8573-1:2010 [-:::]<br>Inert gases                                                              |
| Corrosion resistance class CRC                        | 2 - Moderate corrosion stress                                                                                        |
| LABS (PWIS) conformity                                | VDMA24364-B1/B2-L                                                                                                    |
| Air purity class at output                            | Compressed air to ISO 8573-1:2010 [6:8:4]<br>Inert gases                                                             |
| Media temperature                                     | -10 °C ... 60 °C                                                                                                     |
| Ambient temperature                                   | -10 °C ... 60 °C                                                                                                     |
| Product weight                                        | 5400 g                                                                                                               |
| Type of mounting                                      | Either:<br>In-line installation<br>With accessories                                                                  |
| Pneumatic connection, port 1                          | G1/2                                                                                                                 |
| Pneumatic connection, port 2                          | G1/2                                                                                                                 |
| Material housing                                      | Die-cast zinc                                                                                                        |
| Material bowl                                         | PC                                                                                                                   |