



## Technical datasheet

### NU1048C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, floating, separable, brass cage

#### Visual(s)



#### Product definition

|                               |         |
|-------------------------------|---------|
| <b>d</b>                      | 240 mm  |
| <b>D</b>                      | 360 mm  |
| <b>B</b>                      | 56 mm   |
| <b>E</b>                      | 330 mm  |
| <b>F</b>                      | 270 mm  |
| <b>rs min</b>                 | 3 mm    |
| <b>r1s min</b>                | 3 mm    |
| <b>Radial clearance class</b> | C3      |
| <b>Mass (without HJ ring)</b> | 19.7 kg |
| <b>Brand</b>                  | NTN     |

#### Product performance

|                                        |           |
|----------------------------------------|-----------|
| <b>Dynamic load, C</b>                 | 530 kN    |
| <b>Static load, C0</b>                 | 820 kN    |
| <b>Fatigue limit load, Cu</b>          | 71.9 kN   |
| <b>Nlim (oil)</b>                      | 2,100 rpm |
| <b>Nlim (grease)</b>                   | 1,800 rpm |
| <b>Min operating temperature, Tmin</b> | -40 °C    |
| <b>Max operating temperature, Tmax</b> | 120 °C    |

## Abutment dimensions

|                |        |
|----------------|--------|
| <b>da min</b>  | 253 mm |
| <b>da max</b>  | 268 mm |
| <b>db min</b>  | 275 mm |
| <b>Da max</b>  | 347 mm |
| <b>ra max</b>  | 2.5 mm |
| <b>r1a max</b> | 2.5 mm |

## Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$