

**FAG****1308-K-TVH-C3** [🔗](#)

Self-aligning ball bearing

Self-aligning ball bearing 13..-K-TVH, tapered bore taper 1:12, plastic cage

Technical information



Main Dimensions & Performance Data

d	40 mm	Bore diameter
D	90 mm	Outside diameter
B	23 mm	Width
C _r	30.000 N	Basic dynamic load rating, radial
C _{0r}	9.700 N	Basic static load rating, radial
C _{ur}	610 N	Fatigue load limit, radial
n _G	8.600 1/min	Limiting speed
n _{gr}	7.200 1/min	Reference speed
≈m	0,69 kg	Weight

Mounting dimensions

d _{a min}	49 mm	Minimum diameter shaft shoulder
d _{a max}	55 mm	Maximum diameter shaft shoulder
D _{a max}	81 mm	Maximum diameter of housing shoulder
d _{b min}	44 mm	Minimum cavity diameter of the sleeve
B _{a min}	5 mm	Minimum cavity width of the sleeve
r _{a max}	1,5 mm	Maximum fillet radius

Dimensions

r _{min}	1,5 mm	Minimum chamfer dimension
D ₁	74,71 mm	Shoulder diameter outer ring
d ₁	57,75 mm	Shoulder diameter inner ring

Temperature range


T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.



View product details on medias

13.11.2024, 12:36:56 IST

SCHAEFFLER



Calculation factors

e	0,25	Limiting value of Fa/Fr for the applicability of diff. Values of factors X and Y
Y ₁	2,51	Dynamic axial load factor
Y ₂	3,88	Dynamic axial load factor
Y ₀	2,63	Static axial load factor

Additional information

H308	Adapter sleeve
------	----------------