

TECHNICAL DATASHEET

Update : 26/02/2019

DOUBLE CIRCULAR BANJO COUPLER 2 PORTS

GISS

Description

Pressure: 15 bars . Operating temperature: -20 to +80°C . Industrial vacuum -100 kpa . NBR Seal. . H
Polymer and nickel-plated brass body



Characteristics

Ref.	EAN	Exterior tube diameter mm	Connecting diameter "	Execution	Material	Temperature area °C
859896	3660338148620	4	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859897	3660338148637	4	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859898	3660338148644	6	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859899	3660338148651	6	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859900	3660338148668	8	G1/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859901	3660338148675	8	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859902	3660338148682	8	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859903	3660338148699	10	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859904	3660338148705	10	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859905	3660338148712	10	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859906	3660338148729	12	G1/4	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859907	3660338148736	12	G3/8	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80
859908	3660338148743	12	G1/2	Cylindrical	Body in H polymer/ nickel-plated brass	-20/+80