


SL192330-TB-BR

Cylindrical roller bearing

Schaeffler ID:
0535319490000

Cylindrical roller bearing SL1923, full compl, roller set self-retaining, single row, semi-locating bearing, 2 ribs on outer ring, 1 rib on inner ring, type SL19

Technical information



Main Dimensions & Performance Data

d	150 mm	Bore diameter
D	320 mm	Outside diameter
B	108 mm	Width
C _r	1,490,000 N	Basic dynamic load rating, radial
C _{0r}	1,900,000 N	Basic static load rating, radial
C _{ur}	235,000 N	Fatigue load limit, radial
n _G	1,350 1/min	Limiting speed
n _{gr}	840 1/min	Reference speed
	41.8 kg	{Weight}

Dimensions

D ₁	263.5 mm	Shoulder diameter outer ring
D _{a max}	263.5 mm	Maximum diameter of housing shoulder
d ₁	203.3 mm	Shoulder diameter inner ring
d _{a min}	182 mm	Minimum diameter shaft shoulder
d _{c min}	203 mm	Minimum shaft shoulder
F	182.5 mm	Raceway diameter inner ring
r _{a max}	4 mm	Maximum fillet radius
r _{min}	4 mm	Minimum chamfer dimension
s	7 mm	Axial displacement

Temperature range

T _{min}	-30 °C	Operating temperature min.
T _{max}	120 °C	Operating temperature max.