

Series NVFS2000:Base Mounted Type

How To Order

Porting

	Side
※B	Bottom
※ 1/8NPTF only	

Option

	None
Z	With indicator light and surge voltage suppressor

Body type

O-Plug In



Electrical entry

F-Through base



Port size





Without subplate			
01T	1/8NPTF	Plug-in (With Terminal) block std.	 Note 1) Cv factor 0.7
02T	1/4NPTF		Note 1) Cv factor 0.83

※ Bottom ported 1/8NPTF only.
(See pg. 22 for individual subplate part nos.)

Plug-in NVFS2 2 00 5 F 01T

Non plug-in NVFS2 2 10 5 D 02T

Symbol

1	2 position single	
2	2 position double	
3	3 position closed center	
4	3 position exhaust center	
5	3 position pressure center	
6	3 position perfect	

Body type

1-Non plug-in



Pilot operator

Internal

※ R External

※ Special Order

Voltage

1	100VAC ¹⁾ 50Hz
2	200VAC ¹⁾ 50Hz
3	110VAC ¹⁾ 60Hz
4	220VAC ¹⁾ 60Hz
5	24VDC
6	12VDC
9	Others (Note 1)

※ Special Order

Note 1) Indicate in parentheses at end of part no.
Ex. (AC24V).

Port size

Without subplate			
01T	1/8 NPTF	Non plug-in	Note 1) Cv factor 0.7
02T	1/4 NPTF		Note 1) Cv factor 0.83

Option

	None
Z†	With indicator light and surge voltage suppressor
S	With surge voltage suppressor
※ Special for grommet type G only.	
†Z option N/A for grommet type G.	

Electrical entry

G-Grommet	D-DIN connector	T-Conduit terminal	E-Grommet terminal
			
※ Special Order.			