How to Order

AMG150C to 550C



Body size

AMG 550C

150C
250C
350C
450C
550C

Thread type

Symbol	Type
Nil	Rc
F	G*1
N	NPT

*1 Conforms to ISO1179-1.

Port size

Cumbal	Size	Applicable body size				
Symbol		150C	250C	350C	450C	550C
01	1/8					
02	1/4	•	•			
03	3/8		•	•		
04	1/2			•	•	
06	3/4					•
10	1					•

Accessory

	Accessiy
Symbol	Description
Nil	_
В	Bracket *2

*2 Bracket is included, (but not assembled).

Made to Order

("How to Order" and the applicable models are different from those shown on this page. Be sure to refer to "Made to Order".)

Symbol Description		Page for details
Nil —		_
X15	With IN-OUT flange	P.69
X26	N.C., N.O. auto drain, drain piping type	P.70

Option *3

Symbol	ol Description —		
Nil			
F	Rubber material: Fluororubber		
Н	For medium air pressure (1.6 MPa)		
J	Drain guide 1/4 female threaded *4		
R	 R IN-OUT reversal direction V Degreasing wash,*5 white vaseline 		
V			

- *4 Drain piping and piping for a stop valve such as ball valve are required.
- *5 Only body/housing is degreasing washed.

Auto drain *3

Symbol	Description		
Nil	Drain cock (Without auto drain)		
С	C N.C. auto drain		
D	N.O. auto drain		

*3 Refer to "Auto Drain Specifications/ Option Combinations".

Auto Drain Specifications/Option Combinations

- △: Plural options cannot be selected.
 - (i.e. Combinations such as C-FV, D-FHV are not possible.)

Symbol	F	Н	R	V
Auto drain specifications NiI	0	0	0	0
С	\triangle		0	
D	\triangle	\triangle	0	\triangle
J	0	0	0	0

Options

Symbol F: Rubber material: Fluororubber

Fluororubber is used for the parts such as O-ring and gasket.

Symbol R: IN-OUT reversal direction

Air flow in the separator is changed to right to left.

(Air flow direction of the standard: Left to right.)

Symbol H: For medium air pressure (1.6 MPa)

Can be used up to 1.6 MPa at maximum.

Symbol V: Degreasing wash, white vaseline

Body/housing is degreasing washed. The lubrication grease for O-ring and gasket is changed to white vaseline.

Symbol J: Drain guide 1/4 female threaded





