

TECHNICAL DATASHEET

Update : 26/02/2019

GAZ TAP - SPIRAL FLUTE - HSS 3% VANADIUM - MULTI-MATERIAL



Description

GAZ thread . Blind hole taps



Characteristics

Ref.	EAN	Threading (inch)	Threading diameter (inch)	No. of threads per inch	Angle of helix °	Body material	Tolerance	Drilling diameter mm	Tail diameter mm	Square drive adapter mm
864940	3660338193781	BSP	1/8	28	40	HSSE 3% Vanadium	ISO229	8,7	7	5,5
864941	3660338193798	BSP	1/4	19	40	HSSE 3% Vanadium	ISO229	11,8	11	9
864942	3660338193804	BSP	3/8	16	40	HSSE 3% Vanadium	ISO229	15,25	12	9
864943	3660338193811	BSP	1/2	14	40	HSSE 3% Vanadium	ISO229	19	16	12
864944	3660338193828	BSP	5/8	14	40	HSSE 3% Vanadium	ISO229	21	18	14,5
864945	3660338193835	BSP	3/4	14	40	HSSE 3% Vanadium	ISO229	24,5	20	16
864946	3660338193842	BSP	1	11	40	HSSE 3% Vanadium	ISO229	30,75	25	20