


Take-up housing units

For linear motion
With grub screws in inner ring



UCT

Dimension table (continued) · Dimensions in mm and inch											
Designation			Mass m ≈ kg	Dimensions							
Unit	Housing	Radial insert ball bearing		d		H	L	L ₁	L ₂	L ₃	A
				mm	inch						
UCT208-24	T208	UC208-24	2,36	38,1	1 ¹ / ₂	114	144	88	16	83	49
UCT208-25	T208	UC208-25	2,33	39,688	1 ⁹ / ₁₆	114	144	88	16	83	49
UCT208	T208	UC208	2,32	40	–	114	144	88	16	83	49
UCT209-26	T209	UC209-26	2,46	41,275	1 ⁵ / ₈	117	144	87	16	83	49
UCT209-27	T209	UC209-27	2,42	42,863	1 ¹¹ / ₁₆	117	144	87	16	83	49
UCT209-28	T209	UC209-28	2,38	44,45	1 ³ / ₄	117	144	87	16	83	49
UCT209	T209	UC209	2,37	45	–	117	144	87	16	83	49
UCT210-29	T210	UC210-29	2,64	46,038	1 ¹³ / ₁₆	117	149	90	16	86	49
UCT210-30	T210	UC210-30	2,59	47,625	1 ⁷ / ₈	117	149	90	16	86	49
UCT210-31	T210	UC210-31	2,54	49,213	1 ¹⁵ / ₁₆	117	149	90	16	86	49
UCT210	T210	UC210	2,52	50	–	117	149	90	16	86	49
UCT210-32	T210	UC210-32	2,5	50,8	2	117	149	90	16	86	49
UCT211-32	T211	UC211-32	3,98	50,8	2	146	171	106	19	95	64
UCT211-33	T211	UC211-33	3,93	52,388	2 ¹ / ₁₆	146	171	106	19	95	64
UCT211-34	T211	UC211-34	3,87	53,975	2 ¹ / ₈	146	171	106	19	95	64
UCT211	T211	UC211	3,83	55	–	146	171	106	19	95	64
UCT211-35	T211	UC211-35	3,81	55,563	2 ³ / ₁₆	146	171	106	19	95	64
UCT212-36	T212	UC212-36	4,84	57,15	2 ¹ / ₄	146	194	119	19	102	64
UCT212-37	T212	UC212-37	4,77	58,738	2 ⁵ / ₁₆	146	194	119	19	102	64
UCT212	T212	UC212	4,71	60	–	146	194	119	19	102	64
UCT212-38	T212	UC212-38	4,69	60,325	2 ³ / ₈	146	194	119	19	102	64
UCT212-39	T212	UC212-39	4,61	61,913	2 ⁷ / ₁₆	146	194	119	19	102	64