

FRD MINI

Recessed mini fire rated, Downlight



Features:

Compact fire rated downlight with AC on board driver technology

White, matt white, satin nickel or polished chrome available

Dimmable as standard

Loop in/out mains connections

Steel body providing a high level of fire protection in accordance with Building Regulations Part B

30, 60 & 90 minute fire rating with solid timber joists

30 minute fire rating with Staircraft I-Joist and METAL WEB Joist (COMPATABILITY MATRIX)

30,000 hours lifetime [L70/B50]

Construction:

Convert to larger sized cut outs with the [CONVERSION PLATES](http://www.xcitedlighting.co.uk/products/frd-conversion-plate/)

Up to 90 lumens per watt efficacy



FRD MINI

Recessed mini fire rated, Downlight

Order Codes

All dimensions are in millimetres

Order Code	Description	Lumens(lm)	Total Power(W)	Efficacy(lm/W)	Weight(Kg)
XCFRA5WWW	5W recessed FRD - 3000K - white trim	400	5	80	0.20
XCFRA5WMMW	5W recessed FRD - 3000K - matt white trim	400	5	80	0.20
XCFRA5WWSN	5W recessed FRD - 3000K - satin nickel trim	400	5	80	0.20
XCFRA5NWPC	5W recessed FRD - 3000K - polished chrome trim	450	5	90	0.20
XCFRA5NWWW	5W recessed FRD - 4000K - white trim	450	5	90	0.20
XCFRA5NMMW	5W recessed FRD - 4000K - matt white trim	450	5	90	0.20
XCFRA5WWSN	5W recessed FRD - 4000K - satin nickel trim	400	5	80	0.20
XCFRA5NWPC	5W recessed FRD - 4000K - polished chrome trim	450	5	90	0.20

Dimensions

All dimensions are in millimetres

Order Code	Diameter	C	Cut Out
XCFRA5WWW	80	80	60
XCFRA5WMMW	80	80	60
XCFRA5WWSN	80	80	60
XCFRA5NWPC	80	80	60
XCFRA5NWWW	80	80	60
XCFRA5NMMW	80	80	60
XCFRA5WWSN	80	80	60
XCFRA5NWPC	80	80	60

