

Part number

PES 1663 PV



mobile socket outlet, PLUSO series, SQUICH® quick connection, 2 poles + PE, 6 h (blue), 16 A, 200 ÷ 250 V

Product description

Product type	socket mobile
Series	PES....PV, PLUSO SQUICH®
Connection type	SQUICH® quick connection
N. of poles	2 poles + 
Clock position	6

Technical data

Current	16 A
Voltage	200 ÷ 250 V
IP degree of protection	IP44

Further technical details

Weight	132,00 g
Operating temperature range (min, max)	-40°C ... +125°C

Approvals / Standards

Reference standard	EN 60309-1 and -2
---------------------------	-------------------

General ordering information

EAN13 code	8015747101851
-------------------	---------------

Packaging Information


Packaging length	400,00 mm
Packaging height	410,00 mm
Packaging width	400,00 mm
Packaging weight	13,55 kg
Packaging volume	65,60 dm³
Packaging description	Carton box
Packaging quantity	100 Pcs
Packaging EAN code	8015747113052

Part number

PES 1663 PV



Catalogue drawings



Notes

Dimensions shown in mm are not binding and may be changed without notice.

- Compliant with EN 60309-1 and -2
- Enclosure, insert and spring lid in insulating, thermoplastic, self-extinguishing material
- PES...PV types (IP44), RAL 7035 grey enclosure, spring lid colour coded according to the operating voltage, entry with cable gland
- PESW...PV types (IP66/IP67), RAL 7035 grey enclosure, spring lid with locking ring and gasket colour coded according to the operating voltage, entry with cable gland
- Terminals with retained screws
- IP44 and IP66/IP67 degrees of protection (EN 60529)

