

TECHNICAL DATASHEET

Update : 26/02/2019

UNC TAP - RIGHT HAND THREAD - HSS - 3% VANADIUM MULTI-MATERIALS



Description

UNC thread . Through hole tap



Characteristics

Ref.	EAN	Threading (inch)	Threading diameter (inch)	No. of threads per inch	Total length mm	Body material	Tolerance	Drilling diameter mm	Tail diameter mm	Square drive adapter mm
864955	3660338193927	UNC	6	32	56	HSSE 3% Vanadium	2B	2,7	4	3
864956	3660338193934	UNC	8	32	63	HSSE 3% Vanadium	2B	3,5	4,5	3,4
864957	3660338193941	UNC	10	24	70	HSSE 3% Vanadium	2B	3,8	6	4,9
864958	3660338193958	UNC	12	24	80	HSSE 3% Vanadium	2B	4,5	6	4,9
864959	3660338193965	UNC	1/4	20	80	HSSE 3% Vanadium	2B	5,1	7	5,5
864960	3660338193972	UNC	5/16	18	90	HSSE 3% Vanadium	2B	6,5	8	6,2
864961	3660338193989	UNC	3/8	16	90	HSSE 3% Vanadium	2B	7,9	9	7
864954	3660338193910	UNC	5	40	56	HSSE 3% Vanadium	2B	2,65	3,5	2,7
864962	3660338193996	UNC	7/16	14	100	HSSE 3% Vanadium	2B	9,3	8	6,2
864963	3660338194009	UNC	1/2	13	110	HSSE 3% Vanadium	2B	10,7	9	7
864964	3660338194016	UNC	9/16	12	110	HSSE 3% Vanadium	2B	12,3	11	9
864965	3660338194023	UNC	5/8	11	110	HSSE 3% Vanadium	2B	13,5	12	9
864966	3660338194030	UNC	3/4	10	125	HSSE 3% Vanadium	2B	16,5	14	11
864967	3660338194047	UNC	7/8	9	140	HSSE 3% Vanadium	2B	19,3	18	14,5
864968	3660338194054	UNC	1	8	160	HSSE 3% Vanadium	2B	22,25	18	14,5
867024	3660338210617		4		56				3,5	2,7