




Technical datasheet

NJ228C3

Single row cylindrical roller bearings

Single row cylindrical roller bearing, single direction for axial loads, separable, pressed steel cage.

Visual(s)



Product definition

d	140 mm
D	250 mm
B	42 mm
E	221 mm
F	169 mm
d1	179.5 mm
rs min	3 mm
r1s min	3 mm
Radial clearance class	C3
Mass (without HJ ring)	8.68 kg
Brand	NTN

Product performance

Dynamic load, C	310 kN
Static load, C0	400 kN
Fatigue limit load, Cu	39.9 kN
Nlim (oil)	3,100 rpm
Nlim (grease)	2,700 rpm
Min operating temperature, Tmin	-40 °C
Max operating temperature, Tmax	120 °C
Characteristic cage frequency, FTF	0.43 Hz
Characteristic rolling element frequency, BSF	7.37 Hz
Characteristic outer ring frequency, BPF0	7.37 Hz
Characteristic inner ring frequency, BPFI	9.63 Hz

Abutment dimensions

da min	153 mm
da max	166 mm
dc min	182 mm
Da max	237 mm
ra max	2.5 mm

Calculation factors

Equivalent dynamic radial load

$$P = Fr$$

Equivalent static radial load

$$Po = Fr$$