


# Solenoid valve

## VZWD-L-M22C-M-N14-25-V-2AP4-22-R1

Part number: 1491976

FESTO



 General operating condition

## Data sheet

| Feature                          | Value                                                                                                                        |
|----------------------------------|------------------------------------------------------------------------------------------------------------------------------|
| Design                           | Directly actuated poppet valve                                                                                               |
| Type of actuation                | Electric                                                                                                                     |
| Sealing principle                | Soft                                                                                                                         |
| Mounting position                | optional                                                                                                                     |
| Type of mounting                 | In-line installation                                                                                                         |
| Connection Process valve         | 1/4 NPT                                                                                                                      |
| Electrical connection            | Type A<br>Plugs<br>To EN 175301-803<br>Square design                                                                         |
| Nominal size                     | 2.5 mm                                                                                                                       |
| Valve function                   | 2/2-way, closed, monostable                                                                                                  |
| Manual override                  | None                                                                                                                         |
| Flow direction                   | Non-reversible                                                                                                               |
| Medium                           | Compressed air to ISO 8573-1:2010 [7:4:4]<br>Inert gases<br>Mineral oil<br>Water<br>Neutral fluids<br>Other media on request |
| Nominal pressure PN              | 100                                                                                                                          |
| Pressure difference              | 0 MPa                                                                                                                        |
| Pressure difference              | 0 bar                                                                                                                        |
| Pressure difference              | 0 psi                                                                                                                        |
| Characteristic coil data         | 110 V AC: 50/60 Hz, pick-up power 19.0 VA, holding power 16.0 VA                                                             |
| Insulation material class        | F                                                                                                                            |
| Permissible voltage fluctuations | +/- 10 %                                                                                                                     |
| Duty cycle                       | 100%                                                                                                                         |
| Type of reset                    | Mechanical spring                                                                                                            |
| Type of piloting                 | Direct                                                                                                                       |
| Symbol                           | 00992979                                                                                                                     |
| Medium pressure                  | 0 MPa ... 2.2 MPa                                                                                                            |

| Feature                                    | Value                                      |
|--------------------------------------------|--------------------------------------------|
| Medium pressure                            | 0 bar ... 22 bar                           |
| Medium pressure                            | 0 psi ... 319 psi                          |
| Max. viscosity                             | 22 mm <sup>2</sup> /s                      |
| Media temperature                          | -10 °C ... 80 °C                           |
| Ambient temperature                        | -10 °C ... 35 °C                           |
| Leakage rate to EN 12266-1                 | A                                          |
| Flow rate Kv                               | 0.16 m <sup>3</sup> /h                     |
| Standard nominal flow rate                 | 170 l/min                                  |
| Switching time on                          | 20 ms                                      |
| Switching time off                         | 18 ms                                      |
| Note on materials                          | RoHS-compliant                             |
| LABS (PWIS) conformity                     | VDMA24364 zone III                         |
| Material housing                           | High-alloy stainless steel                 |
| Material number housing                    | 1.4305                                     |
| Material seals                             | FPM                                        |
| Product weight                             | 650 g                                      |
| CE mark (see declaration of conformity)    | To EU Low Voltage Directive                |
| CE marking (see declaration of conformity) | To UK regulations for electrical equipment |
| Degree of protection                       | IP65                                       |
| Corrosion resistance class CRC             | 3 - high corrosion stress                  |